

# AC-26 Brake Fluid DOT 3

## Premium Grade DOT 3 Brake Fluid

PRODUCT DATA SHEET

**Use -** AC-26 is a premium quality brake fluid suitable for applications where manufacturers specify DOT 3 is required.

### PRODUCT INFORMATION

AC-26 is a premium quality, non silicone, non-mineral/petroleum based, fully synthetic brake fluid designed for use in a wide range of brake and clutch applications.

AC-26 is recommended for re-fill or top-up of brake and clutch systems in passenger cars, 4WD's, motorcycles, light and heavy duty commercial vehicles, mining, construction and agricultural equipment that require a non petroleum based DOT 3 brake & clutch hydraulic fluid. AC-26 is suitable for use where the vehicle manufacturer specifies DOT 3 brake fluid. Dot 3 brake fluid should be changed according to the manufacturers service specifications.

Conforms to the following:

Australian Standard AS 1960-2005 Grade 1  
FMVSS 116 DOT 3  
ISO 4925 Class 3  
SAE J 1703



### TYPICAL PROPERTIES

<b>Appearance:</b>	Amber Liquid
<b>Odour:</b>	Slight Odour
<b>pH:</b>	7.5 - 8.5
<b>ER Boiling Point:</b>	240°C - 260°C
<b>Wet ERBP °C min.</b>	150°C
<b>Solubility:</b>	Soluble
<b>Hazard Class:</b>	Non Hazardous Substance
<b>DG Class:</b>	Non Dangerous Goods
<b>Flash Point:</b>	137°C
<b>Reserve Alkalinity:</b>	52.00

Non DG

### DIRECTIONS FOR USE

1. Clean and flush system prior to refilling
2. Add fluid in accordance to vehicle manufacturer's recommendation.
3. Reseal container immediately after to avoid contamination and absorption of moisture.

**IMPORTANT:**

- \* Do not allow contact with paintwork.
- \* Do not mix brake fluids.
- \* Dispose of empty containers properly. Do not use empty container for storing other fluids.

### PRODUCT CODES / QUANTITIES

A/AC26/(500)	500mL Hand Grenade (Carton of 12)
A/AC26/5	5L Plastic Bottle (Carton of 4)
A/AC26/20	20L Plastic Cube
A/AC26/200	200L Metal Drum
A/AC26/IBC	1000L IBC