GP Series

GP 12340 Datasheet

12V Top Terminal VRLA-AGM

Specifications	
Voltage (Vdc)	12
Nominal Capacity (1.75 VPC @25°C)	34 Ah @20hr-rate
Ah Capacity (8-Hr 1.75 VPC @ 25°C)	34.7
Ah Capacity (20-Hr 1.75 VPC @ 25°C)	37.6
Ah Capacity (8-Hr 1.80 VPC @ 25°C)	34.1
Max Charge Current (A)	10.2
Max Discharge Current (A)	380
Short Circuit Current (A)	915
Internal Resistance (mΩ)	Approx. 9.5
Terminal Type	B5 terminal to accept M6 bolt
Terminal Torque	51.7±10.3 Kgf·cm / 44.9±9.0 Lbf·in / 5.10±1.0 N·m
Container Material	ABS (UL 94-HB) & Flame Retardant (94-V0) available upon request.
Weight (kg. / lb., Approx.)	10.48 / 23.10
Length (L) (mm / in)	195.6±2.0 / 7.70±0.08
Width (W) (mm / in)	130.0±1.5 / 5.12±0.08
Height (H) (mm / in)	178.3±2.0 / 7.02±0.08
Design Life	Up to 5 Years in Standby Service at 25°C Eurobat (20°C): 3-5 Years Standard Commercial
Operating Temperature	Nominal: 25°C (77°F) Discharge: -15°C - 50°C (5°F-122°F) Charge/Storage: -15°C - 40°C (5°F – 104°F)
Float Charging Voltage	13.5 - 13.8 Vdc/battery 25°C (77°F)
Eq. Charging Voltage	14.4 - 15.0 Vdc/battery 25°C (77°F)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F); Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).



Valve Regulated Lead Acid (VRLA) Battery

Maintenance-Free, Absorbent Glass Mat (AGM) Technology for Efficient Gas Recombination of up to 99%

Pure Lead Construction and Proprietary Elements

Designed for Float Service Standby Power Applications

Built in Accordance with IEC 61056-1/2:2012 and UL1989 Recognized (MH14533)

MH14533


GP Series


GP 12340 Datasheet


12V Top Terminal VRLA-AGM


Constant Current Discharge Characteristics Unit: A (25°C, 77°F)												
F.V/Time	**5MIN**	**10MIN**	**15MIN**	**30MIN**	**60MIN**	**90MIN**	**2HR**	**3HR**	**5HR**	**8HR**	**10HR**	**20HR**
10.02V (1.67 VPC)	134	95.5	72.8	42.6	24.7	17.9	14.2	10.2	6.62	4.37	3.58	1.90
10.50V (1.75 VPC)	112	84.2	67.9	41.1	24.1	17.6	14.0	10.0	6.54	4.33	3.55	1.88
10.80V (1.80 VPC)	99.9	75.6	62.4	39.3	23.4	17.1	13.7	9.91	6.43	4.26	3.49	1.86

Constant Power Discharge Characteristics Unit: W (25°C, 77°F)												
F.V/Time	**5MIN**	**10MIN**	**15MIN**	**30MIN**	**60MIN**	**90MIN**	**2HR**	**3HR**	**5HR**	**8HR**	**10HR**	**20HR**
10.02V (1.67 VPC)	1339	1014	804	511	299	216	171	122	79.1	52.4	43.0	22.9
10.50V (1.75 VPC)	1198	925	757	494	293	213	169	120	78.4	52.0	42.6	22.7
10.80V (1.80 VPC)	1088	852	702	475	285	209	167	119	77.4	51.3	42.1	22.5









11F, No. 150, Sec. 4, Chengde Rd., Shilin Dist., Taipei City 111052, Taiwan (R.O.C.)
Tel: +886-2-2880-5600 Mail: service@csb-battery.com.tw