

# MACHINE ROUNDED POLES

Machine Round Poles are uniformed in diameter (same diameter) and are specifically designed for visual appearance where uniformity is required. Feedstock goes through a different process from SED Poles, where it is put through a Machine Rounder (not a Pole Peeler) to come out the same diameter down the whole length.

Roundwood New Zealand Machine Round Poles are available in the following lengths: 1.8m, 2.1m, 2.4m, 2.7m, 3.0m, 3.6m, 4.2m, 4.8m, 5.4m, 6.0m, 7.0m, 8.0m and 9.0m.

They are also available in the following diameters: 155mm, 170mm, 185mm and 200mm.

Roundwood New Zealand Machine Round Poles are then put through our Steam Drying process, which allows us to get an even penetration and retention of CCA chemical in the Treating process. Poles are Pressure Treated to H5 Hazard Class in accordance with New Zealand Standards (NZS) NZS3640. Once Poles have been treated they are stored on the Drip off Pad to allow Fixation to occur. Fixation is achieved when the chemical is dry on the wood and no more leaching of chemical can occur.

In any situation where a machine uniformed appearance is required, Roundwood New Zealand's Machine Round Poles are the suitable solution.

## Use Roundwood New Zealand Machine Round Poles for:

- Retaining Walls where Appearance is particularly important.
- Construction and Farm Buildings where a dimensionally consistent product and appearance is important.
- Any Application that requires a Uniformed Finish

## Roundwood New Zealand Quick Reference:

- Radiata Pine Machine Round Uniformed Diameter
- Available Lengths: 1.8m to 9.0m
- Diameter Range: 155mm, 170mm, 185mm and 200mm
- H5 CCA Hazard Class
- H6 CCA Marine Hazard Class
- Complies with New Zealand Standards NZS3605 and NZS3640

