

UN-PEELED NATURAL POLES

Unpeeled Natural Poles are naturally tapered Poles that are left in their natural debarked form. These are used specifically for foundation piling for ground stabilisation. They have not had any of the outer cambium layer removed through the peeling process so provide a rougher finish for greater skin friction, as well as being slightly stronger than an SED Machine Peeled Construction Pole. This also allows the Machine Peeling cost to be saved. Unfortunately, what you gain in strength you compromise in looks so they are only suitable for applications where they are unseen.

Roundwood New Zealand Unpeeled Natural Poles are naturally tapered Radiata Pine Poles that are graded to ensure they meet the New Zealand Standard (NZS) NZS3605; they are also surveyed onsite for even taper and straightness. Unpeeled Natural Poles are put through the same Steam Dry and H5 Hazard Class Treating process as our SED Construction Poles to ensure they comply with New Zealand Standard NZS3640.

Use Roundwood NZ Unpeeled Natural Poles for:

- Foundations
- Ground Improvement and Stabilization
- Installation with Pile Driving and Drilling

Roundwood NZ Quick Info:

- Radiata Pine Debarked only
- Naturally Tapered: 6-8mm per metre
- Diameter range: 150mm to 550mm SED
- Length range: 1.8m to 20m
- H5 Hazard Class CCA Treatment
- H6 Hazard Class CCA Marine available
- Economical option
- Complies with New Zealand Standards NZS3606 and NZS3640

