MODEL TT2000 DRY TENDER





Model TT2000SF Side Auger

· Belly auger extends to bumper for pit dumping!



Model TT2000B Rear Belt

- KSI cleated belt; stainless belly auger
- 38HP gas or Kohler diesel engines
- · Almost twice as fast as auger!



Optional **Split Hoppers** with Full-Height Dividers







(800) 843-5241

www.kbhequipment.com



Bolted Stainless Hopper Cradle

Specifications

Hoppers

- Steep Hopper Slopes Sides = 55 Degrees/ Ends = 40 degrees / Middle = 48 Degrees
- 1,065 Cubic Feet Total Capacity
- Capacity: 24.5 Tons (Urea)
- Dump-In Height: 11'2"
- Lower Center of Gravity
- Stainless Hopper Cradle (Bolted)
- Hoppers Moved Forward Better Weight Distribution On Axles
- Stainless Hopper Divider (Full-Height Divider Reaches Tarp Bows)
- Stainless Hopper Safety/Agitation Ports
- Stainless Hopper Grates

Augers

- Stainless Augers & Shafts
- Stainless Two-Piece Bolted Auger Couplers
- Discharge Auger Hanger Bearing: Bronze Bushing
- Discharge Auger Lower Bearing: Stainless
- Reversible Discharge Auger With Pressure Check
- · Remote Grease Zerk Station
- Hydraulic Poly Cleanout Doors
- Hydraulic Vibrators
- Discharge Auger Cleanout Water Hose Fitting
- · Unload Rate: 2-3 Tons Per Minute
- · Unload Heights:

Rear Discharge Model:

Maximum: 15′ 5″ (7′ 1″ Reach From Bumper) Minimum: 8′ 11″ (10′ 1″ Reach From Bumper)

Side Discharge Model:

Maximum: 15' 6" (10' 1" Reach From Fender) Minimum: 9' 9" (13' 7" Reach From Fender)

Trailer

- Empty Weight 14,760 lbs.
- Polyurethane Enamel Paint With Epoxy Primer
- Hutch Cast Iron Axle Hangers
- Stainless Rear and Front Fenders
- · Stainless Engine Cover
- Stainless Axle/Air Tank Cover





Stainless Hopper Grates



Auger Transport Alarm



Hydraulic Vibrators



Water Cleanout Fitting



Rear Fenders and Axle Cover



Front Fenders



Safety/Agitation Ports



Steep Hopper Slopes



Two-Piece Bolted Auger Couplers



Remote Grease Zerk Station



SRT Spring Assist Tarp/Optional Electric



Standard Stainless/Optional Poly-cupped