

## KEY BENEFITS

- **Universal HUB flexibility:** Ships direct-thread but converts to 1.375×24 Universal HUB to fit most muzzle devices.
  - **Designed for maneuverability:** Slim profile and balanced mass reduce handling impact.
  - **Industry-leading suppression:** Internal flow geometry reduces blast and shooter-facing gases for clearer sight picture.
  - **Full-auto rated:** Inconel 718 construction for heavy cyclic use.
  - **Field-serviceable:** Removable end cap for quick in-the-field replacement after an impact.
  - **Durable finish:** Cerakote C Series (Black) for lasting corrosion resistance.
- 

## TECHNICAL SPECIFICATIONS (TABLE / COMPACT LIST)

- **Full-Auto Rated:** Yes
- **Length (can w/o direct-thread hub):** 7.254 in
- **Overall length (can w/ direct-thread hub):** 7.75 in
- **Outer Diameter (OD):** 1.526 in
- **Weight (can w/o direct-thread hub):** 13.4 oz
- **Weight (can w/ direct-thread hub):** 15.4 oz
- **Materials:** Inconel 718 **1.375"-24**
- **Coating:** Cerakote C Series (Black)
- **Mount / Thread:** Ships with **1/2"-28 direct-thread HUB** ; removable to **Universal HUB**
- **Maximum muzzle break lengthaccommodated:** 3.35in
- **Field-serviceable end cap:** Yes — removable anduser-replaceable

### SUPPORTEDCALIBERS:

5.56, .223 Rem, .223 Wylde, .224 Valkyrie, .222 Rem, .204 Ruger, .22 Nosler, .22 LR, .22 WMR, .17 HMR, 6mm ARC, .22 ARC, .22-250 Rem.

---