



油之陆 CVTF NS-2

无段变速箱油无段变速箱油采用高性能全合成基础油和精心挑选的添加剂混合而成，这里面包括摩擦改进剂、洗涤分散剂、氧化抑制剂、粘度指数改进剂、腐蚀抑制剂和消泡剂。

这是一种新型多车型自动变速箱油，专为最新一代无段变速器(CVT)设计，该变速器通过钢制牵引链或皮带传递牵引力。与普通自动变速器相比，它提供了出色的动力传动比和更好的燃油经济性。

优点 / 用途

- > 提供卓越的摩擦、抗氧化和热稳定性
- > 出色的油膜厚度和抗磨性能
- > 卓越的剪切稳定性，实现一致的位移
- > 与多种密封件兼容

规格、认证及推荐

> 奥迪/大众	P/N G 052 180 (-A2)
> 奥迪/大众	P/N G 052 516 A2
> 宝马/ MINI/ PUNCH	EZL 799
> 宝马/ MINI/ PUNCH	EZL 799A
> 宝马	P/N 83 22 0 136 376
> 宝马	P/N 83 22 0 429 154
> 克莱斯勒 / FCA	MOPAR CVTF+4 P/N 05191184A
> DAIHATSU	AMMIX CVTF- DFE
> DAIHATSU	AMMIX CVTF- DTC
> 道奇/吉普	NS-2
> FCA	CVTF+4 P/N 05191184AA
> 福特	CFT23
> 福特	CFT30
> 福特	MERC C
> 福特	WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
> 通用汽车	CVTF I-GREEN2
> 通用汽车	CVT P/N 19260800
> 通用汽车	DEX-CVT
> 本田	CVTF P/N 08200-9006
> 本田	HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
> 本田	HCF-2 P/N 08200-HCF2

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warrantied of MERCHANTABILITY and FITNESS.

Ver 15/1



US LUBE®
Advance Technology • Superior Value

规格、认证及推荐

> 马自达	CVTF 3320
> MINI COOPER	ZF CVT V1
> 三菱	DIAMOND GREEN CVTF-J1
> 三菱	DIAMOND GREEN CVTF-J4
> 日产	NS-1
> 日产	NS-2
> 日产	NS-3
> 雷诺	ELFMATIC
> SATURN	P/N 22688912
> SHELL	GREEN IV
> 斯巴鲁	LINEARTRONIC CVTF
> 斯巴鲁	LINEARTRONIC CVTF-II; P/N K0425Y0711
> 斯巴鲁	LINEARTRONIC CV-30 P/N K0425Y0710
> 斯巴鲁	e-CVTF
> 斯巴鲁	i-CVTF
> 斯巴鲁	HIGH TORQUE P/N K0421Y0700
> 铃木	CVT FLUID GREEN 1
> 铃木	CVT FLUID GREEN 2
> 铃木	CVTF 3320
> 铃木	NS-2
> 丰田 / 雷克萨斯	FE
> 丰田 / 雷克萨斯	TC

典型物性

测量项目	测量方法	单位	
比重 @ 15 °C	ASTM D 4052	kg/L	0.8537
闪点 (开口杯)	ASTM D 92	°C	198
倾点	ASTM D 97	°C	-45
运动粘度 @ 40°C	ASTM D 445	cSt	34.4
运动粘度 @ 100°C	ASTM D 445	cSt	7.2
粘度指数	ASTM D 2270	-	180
布氏粘度 @-40°C,mPas.s	ASTM D2983	mPa.s	13500
外观	Visual	-	青色

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.

Ver 15/1