



**US LUBE**<sup>®</sup>  
Advance Technology • Superior Value

25/9/2025  
5392G3ATFREVE2

## 油之陆 ATF MVH

高级全合成自动变速器油采用精选的高粘度指数合成基础油和最新的添加剂技术配制而成，为各种北美、欧洲和亚洲车辆提供优质服务。

该产品推荐用于所有通用汽车 DII、DIII(G)、DIII(H)。同时它也适用于已发布的 JASO 1A 或 艾里逊 C-4 流体规格，并满足丰田 T-IV 级防抖耐久性 (ASD) 的要求。

### 优点 / 用途

- 提供出色的抗氧化和热稳定性，延长使用寿命
- 卓越的磨损保护，保护关键的传动部件
- 优异的粘度稳定性（高 VI），广泛应用于各种汽车变速箱
- 增强极低温度下的流动性

### 规格、认证及推荐

爱信	JWS 3309 ATF, ATF-0T4
艾里逊	389
艾里逊	C2
艾里逊	C3
艾里逊	C4
ATF	3100 PL085
ATF	3403-M115
ATF	ETL-7045 E
ATF	K17
ATF	LA 2634
ATF	N402
ATF	SP-III
宝马	ATF4
宝马	ETL-7045
宝马	ETL-7045 E
宝马	ETL-8072B
宝马	LA 2634
宝马	LT 71141
宝马	P/N 81 22 9 400 272
宝马	P/N 81 22 9 400 275
宝马	P/N 81 22 9 407 858
宝马	P/N 81 22 9 407 859
宝马	P/N 83 22 0 024 249
宝马	P/N 83 22 0 024 359
宝马	P/N 83 22 0 026 922

[www.uslube-chicago.com](http://www.uslube-chicago.com)

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1



**US LUBE**®

Advance Technology • Superior Value

## 规格、认证及推荐

> 宝马	P/N 83 22 0 402 413
> 宝马	P/N 83 22 0 403 248
> 宝马	P/N 83 22 0 403 249
> 宝马	P/N 83 22 2 220 438
> 宝马	P/N 83 22 2 220 440
> 宝马	P/N 83 22 2 220 442
> 宝马	P/N 83 22 7 542 290
> 宝马	P/N 83 22 9 407 765
> 宝马	P/N 83 22 9 407 807
> 博世	BOSCH TE-ML 09
> 雪铁龙	Z 000169756
> 大发	D3-SP
> FCA	ASRC
> FCA	ATF+
> FCA	ATF+2
> FCA	ATF+3
> FCA	ATF+4
> FCA	FIAT 9.55550-AV1
> FCA	FIAT 9.55550-AV4
> FCA	MB 236.10, P/N 05127382AA
> FCA	MB 236.12, P/N 05127382AA
> FCA	P/N 68333587AA
> FCA	SP-III
> FCA	TYPE 7176E
> FCA	TYPE 9602
> 福特	ESP-M2C138-CJ
> 福特	ESP-M2C166-H
> 福特	P/N XT-2-QDX [M]
> 福特	P/N XT-2-QSM [SYN]
> 福特	P/N XT-5-QM [V]
> 福特	P/N XT-5-QSM [V SYN]
> 福特	P/N XT-8-QAW [PREMIUM]
> 福特	P/N XT-9- QMM5 [FNR5]
> 福特	SPEC WSS-M2C922-A1
> 通用汽车	ATF Z1, SATURN P/N 22717466
> 通用汽车	DEX [GM 6032M]
> 通用汽车	DEX-B [GM 6032M]
> 通用汽车	DEX-IIC [6137M]
> 通用汽车	DEX-IID [GM 6137M]
> 通用汽车	DEX-IIIE [GM 6137M]
> 通用汽车	DEX-IIIF [GM 6297M]
> 通用汽车	DEX-IIIG [GM 6417M]
> 通用汽车	DEX-IIIH [GM N10055]
> 通用汽车	P/N 19 40 700
> 通用汽车	P/N 19 40 767
> 通用汽车	P/N 21005966

[www.uslube-chicago.com](http://www.uslube-chicago.com)

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1



# US LUBE®

Advance Technology • Superior Value

## 规格、认证及推荐

> 通用汽车	P/N 88900925
> 通用汽车	P/N 9985010
> 通用汽车	P/N 9986195
> 通用汽车	SATURN T-IV FLUID, SATURN P/N 22689186
> 通用汽车	TYPE A SUFFIX A
> 本田/讴歌	ATF Z1, P/N 08200-9001
> 本田/讴歌	ATF Z1, P/N 08200-9001A
> 现代/起亚	ATF RED-1K
> 现代/起亚	GENUINE ATF
> 现代/起亚	JWS 3314
> 现代/起亚	P/N 00232-19023
> 现代/起亚	P/N 04500-00140
> 现代/起亚	P/N UM040 CH20 RED-1
> 现代/起亚	SP
> 现代/起亚	SP-II
> 现代/起亚	SP-III
> 五十铃	ATF II
> 五十铃	ATF III
> 五十铃	GENUINE ATF
> 五十铃	P/N 08200-9001
> 捷豹	JLM 20238
> 捷豹	JLM 20292
> 捷豹	JLM 21044
> 捷豹	K17, JATCO 3100 PL085
> 捷豹	LT 71141
> 捷豹	WSS-M2C922-A1
> JAMA	JASO M315, CLASS 1-A
> 路虎	ATF N402
> 路虎	JWS3309US
> 曼恩	339A
> 曼恩	339D
> 曼恩	339F
> 马自达	ATF M-5 P/N 0000-23-ATF -M5
> 马自达	ATF N-1
> 马自达	ATF S-1
> 马自达	F-1
> 马自达	JWS3317
> 马自达	M3
> 马自达	TYPE T-IV, JWS 3309 ATF
> 奔驰	A 0019892203
> 奔驰	ATF 3403-M115
> 奔驰	SHEET 236.1
> 奔驰	SHEET 236.10
> 奔驰	SHEET 236.11
> 奔驰	SHEET 236.2
> 奔驰	SHEET 236.5
> 奔驰	SHEET 236.8

[www.uslube-chicago.com](http://www.uslube-chicago.com)

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1



**US LUBE**®

Advance Technology • Superior Value

## 规格、认证及推荐

> 迷你库珀	ATF JWS 3309, P/N 83 22 0 402 413
> 三菱	ATF-J2
> 三菱	DIA QUEEN AW
> 三菱	DII
> 三菱	DIII
> 三菱	SP, P/N MS991156
> 三菱	SP-II
> 三菱	SP-III
> 日产	FLUID A
> 日产	MATIC D
> 日产	MATIC J, P/N 999MP-MTJ00P
> 日产	MATIC K
> 日产	N402
> 标致	P/N Z 000169756
> 保时捷	JWS 3309, P/N 000 043 205 28
> 保时捷	LT 71141
> 保时捷	P/N 000 043 204 41
> 保时捷	P/N 000 043 204 63
> 保时捷	P/N 000 043 305 42
> 保时捷	P/N 958 300 901 00
> 保时捷	P/N 999 917 547 00 (A2) or P/N 000 043 205 09
> PSA	AL4, P/N 9730AE
> PSA	4HP20, P/N 9730AE
> PSA	B71 2340
> 雷诺	DP-0
> 雷诺	MATIC D2
> 雷诺	SATF-D
> 劳斯莱斯	OIL NO. PL 31493PA
> 萨博	ATF HP
> 萨博	JWS 3309
> 萨博	P/N 93 160 393
> SATURN	DEX-IIIIG
> SATURN	T-IV FLUID, P/N 22689186
> 双龙汽车	DSIH 5M-52
> 双龙汽车	DSIH 5M-66
> 斯巴鲁	ATF HP, P/N K0140Y0700, P/N SOA635040
> 铃木	ATF 2326
> 铃木	ATF 2384K
> 铃木	ATF 3314
> 铃木	ATF 3317
> 铃木	ATF 5D06
> 铃木	MATIC D
> 铃木	MATIC J
> 丰田	JWS 3309, TYPE T-IV, P/N 08886-81015
> 丰田	TYPE D-II
> 丰田	TYPE T

[www.uslube-chicago.com](http://www.uslube-chicago.com)

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1



**US LUBE**®  
Advance Technology • Superior Value

## 规格、认证及推荐

> 丰田	TYPE T-II
> 丰田	TYPE T-III
> 沃尔沃	P/N 1161521
> 沃尔沃	P/N 1161621
> 沃尔沃	P/N 1161640; P/N 1161540
> 沃尔沃 CE	97340, AT100
> 沃尔沃 CE	97341, AT101
> 大众/奥迪	G 052 162 (-A1, -A2) [AG4]
> 大众/奥迪	G 052 990 A2
> 大众/奥迪	G 055 025 (-A2)
> 大众/奥迪	G US 000 162
> 大众/奥迪	LT 71141
> ZF	LIFEGUARDFLUID 5 (ZF No. S671 090 170)
> ZF	TE-ML 05L
> ZF	TE-ML 11A
> ZF	TE-ML 11B
> ZF	TE-ML 21L

## 典型物性

测量项目	测量方法	单位	
比重 @ 15 °C	ASTM D 4052	kg/L	0.848
闪点 (开口杯)	ASTM D 92	°C	198
倾点	ASTM D 97	°C	-45
运动粘度 @ 40°C	ASTM D 445	cSt	36.9
运动粘度 @ 100°C	ASTM D 445	cSt	7.0
粘度指数	ASTM D 2270	-	155.6
外观	Visual	-	红色/琥珀色

[www.uslube-chicago.com](http://www.uslube-chicago.com)

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1