



US LUBE[®]
Advance Technology • Superior Value

9/12/2025
4162G3SQA3B4REV1

油之陆 DYNAMICS HERITAGE

全合成乘用车机油采用高品质全合成基础油配制而成，并添加优质添加剂包，可满足长时间运行的发动机的要求。对于高里程车辆，发动机性能通常不会处于最佳状态，车辆会遇到油耗增加、密封泄漏和效率下降等问题。

本产品混合了各种添加剂，有助于恢复旧发动机的性能并延长车辆寿命。曲轴箱助推器和分散剂添加剂也有助于提供更清洁的发动机，并提供更好的磨损保护和齿轮保护。

优点 / 用途

- 提供更好的齿轮保护。
- 专为长时间运行的高里程发动机配制。
- 更好地控制油泥和活塞沉积物。
- 改进油膜厚度可防止因间隙增大而导致的泄漏。

建议用于以下用途

> API	SQ
> ACEA	A3/B4
> 奔驰	226.5
> 奔驰	229.3
> 奔驰	229.5
> PSA	B71 2296
> 雷诺	RN 0710/ 0700
> 大众	502.00/ 505.00

典型物性

测量项目	测量方法	单位	
SAE 粘度等级	SAE J 300	-	5W40
比重 @ 15 °C	ASTM D 4052	kg/L	0.863
闪点 (开口杯)	ASTM D 92	°C	216
倾点	ASTM D 97	°C	-36
运动粘度 @ 40°C	ASTM D 445	cSt	85.2
运动粘度 @ 100°C	ASTM D 445	cSt	14.5
粘度指数	ASTM D 2270	-	177
总碱值	ASTM D 2896	mgKOH/g	14.5

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1