



US LUBE[®]
Advance Technology • Superior Value

14/8/2023
5176G345SPA3B4REV0

油之陆 DYNAMICS SYN ALPHA

全合成乘用车机油特别为现代汽油和柴油乘用车以及轻型柴油卡车而设计，专为满足覆盖欧洲范围的原始设备制造商要求而开发。混合了PAO、酯和高级添加剂让其拥有出色的低温烟灰分散性和出色的高温沉积物控制性，具有自然的高粘度指数和卓越的热稳定性。提供长效发动机服务性能、发动机耐磨性、燃油效率和低温保护。

优点 / 用途

- › 在各种温度和操作条件下均具有超强流动性
- › 提高发动机性能
- › 卓越的高温保护
- › 防止生锈和腐蚀，最大限度延长换油间隔

建议用于以下用途

- › API SP
- › ACEA A3/B4

典型物性

测量项目	测量方法	单位		
SAE 粘度等级	SAE J 300	-	0W30	0W40
比重 @ 15 °C	ASTM D 4052	kg/L	0.847	0.856
闪点 (开口杯)	ASTM D 92	°C	212	216
倾点	ASTM D 97	°C	-42	-42
运动粘度 @ 40°C	ASTM D 445	cSt	69.5	82.2
运动粘度 @ 100°C	ASTM D 445	cSt	11.5	14.1
粘度指数	ASTM D 2270	-	160	178
总碱值	ASTM D 2896	mgKOH/g	12.2	12.2
低温泵送黏度	ASTM D 4684	cP	≤6200	≤6200
硫酸盐灰分含量	ASTM D 874	%wt	≥3.5	≥3.5

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1