



US LUBE®
Advance Technology • Superior Value

26/2/2026

6130G3SQC3VW504507REV2

油之陆 DYNAMICS SYN VK7

全合成优质“Mid SAPS”乘用车润滑油，专为保护汽油和柴油微粒过滤器而配制。它混合了符合 ACEA C3 和 MB-Approval 229.51 要求的高科技核心添加剂。它能广泛地适用于汽油或柴油发动机的现代乘用车和轻型车辆。

该产品提供高温保护，能够达到严格的热分解标准。它可以大大减少发动机表面所积累的积碳，同时保护车辆的废气处理系统。它满足大多数顶级西欧发动机 OEM 的要求，例如梅赛德斯奔驰、大众和宝马，同时也延长了发动机换油的间隔。

优点 / 用途

- 专门用于装有后处理装置的车辆
- 满足众多 OEM 发动机的油品需求
- 在较长的换油周期内提供卓越的性能
- 防止低速早燃 (LSPI)

规格、认证及推荐

➢ API	SQ
➢ ACEA	C3
➢ 宝马	LONGLIFE-04
➢ 奔驰	MB 229.31
➢ 奔驰	MB 229.51
➢ 奔驰	MB 229.52
➢ 欧宝	OV0401547-D30
➢ 欧宝	OV0401547-G30
➢ 保时捷	C30
➢ 大众	VW 504.00
➢ 大众	VW 507.00

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1



US LUBE®
Advance Technology • Superior Value

典型物性

测量项目	测量方法	单位	
SAE 粘度等级	SAE J 300	-	5W30
比重 @ 15 °C	ASTM D 4052	kg/L	0.844
闪点 (开口杯)	ASTM D 92	°C	220
倾点	ASTM D 97	°C	-39
运动粘度 @ 40°C	ASTM D 445	cSt	68.2
运动粘度 @ 100°C	ASTM D 445	cSt	11.8
粘度指数	ASTM D 2270	-	171
总碱值	ASTM D 2896	mgKOH/g	8
低温动力粘度	ASTM D 5293	cP	5139

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1