



*i-Series is  
Smarter Working*



OPTIONS

1

MEDIA INPUT

Paper tray  
PF-P23

OR

Paper tray  
PF-P24

Copier desk  
SCD-5000x

x2

x2



2

MEDIA OUTPUT

Convenience stapler  
EH-T592

LEGEND

Option

Mandatory option

This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES

Duplex

Corner Stapling  
(offline)

DESCRIPTION

MEDIA INPUT	
PF-P23 Paper tray	250 sheets, A4, 60-120 g/m <sup>2</sup>
PF-P24 Paper tray	520 sheets, A4, 60-120 g/m <sup>2</sup>
SCD-5000x Copier desk	Provides storage space for print media and other materials

MEDIA OUTPUT	
EH-T592 Convenience stapler	Convenient stapling of up to 50 sheets per set

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS	
System speed A4	Up to 42 ppm
Autoduplex speed A4	Up to 20 ppm
1st page out time A4	7.2 sec.
Warm-up time	Approx. 25 sec. <sup>1</sup>
Imaging technology	Laser (Class 1 laser product)
Toner technology	Polymerized Toner
Panel size/resolution	1 line LCD
System memory	256 MB (standard/max)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 a/b/g/n
Network protocols	TCP/IP (IPv4 / IPv6); LPD; IPP; SNMP; HTTP; HTTP(S)
Printable paper size	A6-A4; customized paper sizes
Printable paper weight	60-230 g/m <sup>2</sup>
Paper input capacity	620 sheets / 1,660 sheets (standard/max)
Paper tray input (standard)	1x 520; A6-A4; 60-163 g/m <sup>2</sup>
Paper tray input (optional)	1x 250 sheets; A5-A4; 60-120 g/m <sup>2</sup> (up to 2x)
	1x 520 sheets; A5-A4; 60-120 g/m <sup>2</sup> (up to 2x)
Manual bypass	100 sheets; A6-A4; custom sizes; 60-230 g/m <sup>2</sup>
Finishing modes (optional)	Staple (offline)
Automatic duplexing	A4; 60-105 g/m <sup>2</sup>
Output capacity	Up to 150 sheets
Duty cycle (monthly)	Rec. 5,000 pages; Max. <sup>2</sup> 100,000 pages
Toner lifetime	Black up to 18,000 pages
Imaging unit lifetime	Black up to 75,000 pages (imaging unit)
Power consumption	220-240 V / 50/60 Hz; Less than 640 W
System dimension (W x D x H)	373 x 388 x 289 mm (without options)
System weight	Approx. 12.3 kg (without options)

PRINTER SPECIFICATIONS	
Print resolution	1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PostScript 3; XPS; PDF 1.7
Operating systems	Windows 10/11 (32/64);
	Windows Server 2016/2019/2022/2025;
	macOS 11.x - 15.x
Printer fonts	85 PCL Latin; 66 PostScript 3 Emulation Latin; Barcode fonts
Mobile printing	Mopria (Android); WiFi Direct; AirPrint (iOS)

SYSTEM FEATURES	
Security	SSL2; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; Secure print; Kerberos
Accounting	User Function Access Definition; Active Directory support (user name + password + e-mail + smb folder) optional: ID card authentication (ID card reader)
Software	Driver Packaging Utility Download Manager

<sup>1</sup> Warm-up time may vary depending on the operating environment and configuration

<sup>2</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

