

SS2632E

MICRO SCISSOR LIFT



COMPACT DESIGN: 31.9" overall width and 75" overall length makes it easier to navigate tighter jobsites.

CAPACITY: 500 lb platform capacity. Rated for up to 2 occupants (2 in/1 out).

MORE STANDARD FEATURES: Leak containment system helps maintain cleaner jobsites.

SIMPLE MANUAL BRAKE RELEASE SWITCH: Easily release the brakes by rotating the conveniently located switch at the back of the lift with the machine key.

LOW STOWED HEIGHT: A 6'4" stowed height allows the machine to pass through a standard door with the rails folded.



POWER

Charging protection system
Standard FLA batteries

PLATFORM

AC power to platform
Descent alarm
Emergency stop button
Flashing beacons
Horn
Motion alarm
Overload sensing system
Proportional control
Swing gate

CHASSIS

AC drive motors
Automatic braking system
Emergency descent
Emergency stop button
Flashing beacons
Hour meter
Intelligent diagnostic system
Leak containment system
Manual brake release
Over-tilt protection system
Pothole protection
Safety chock for service
Solid non-marking tires
Standard forklift pockets for transport
Swing-out component tray
Telematics ready

OPTIONS

Pipe rack
Perimeter lighting
Telematics



LGMG NA provides an industry-leading 5-year/5,000 hour warranty on new boom lifts, scissor lifts, and vertical mast lifts, and a 3-year/3,000 hour warranty on new telehandlers with an option to purchase an extended warranty upon request.


Terms and conditions apply. Subject to LGMG's warranty policies then in effect. Please visit www.lmgna.com/warranty for details.

SS2632E

MICRO SCISSOR LIFT



	Imperial	Metric
Work Height Max.	30'11"/24'1" (in/out)	9.6 m/7.5 m (in/out)
Ⓐ Platform Height-Raised	24'11"/18'1" (in/out)	7.6 m/5.5 m (in/out)
Ⓑ Platform Length	5'7"	1.7 m
Ⓒ Platform Width	2'5"	0.73 m
Ⓓ Overall Length	6'3"	1.9 m
Ⓔ Overall Width	31.9"	0.81 m
Ⓕ Overall Height-Guardrails Up	7'4"	2.23 m
Ⓖ Overall Height-Guardrails Down	6'4"	1.93 m
Ⓗ Extension Deck	2'11"	0.9 m
Ⓘ Wheelbase	4'7"	1.4 m
Ground Clearance (Stowed/Raised)	3" / 1"	72/20 mm
PRODUCTIVITY		
Max. Platform Occupancy	2 (in) / 1 (out)	
Platform Capacity	500 lb	227 kg
Platform Capacity - Extension	250 lb	113 kg
Drive Height	Full Height	
Gradeability - Stowed	25%	
Outside Turning Radius	6'	1.84 m
Inside Turning Radius	1' 8"	0.51 m
Raise/Lower Speed	31s / 27s	
Drive Speed Stowed/Raised	2.2/ 0.3 mph	3.5/ 0.5 km/h
Max Tilt Rating Fore-Aft/Side-to-Side	3° / 1.5°	
Solid Non-marking Tire Size	12"4"	305x100 mm
Tire Contact Pressure	167 psi	1155 kPa
Occupied Floor Pressure	282 psf	13.5 kPa
POWER		
Power Source (FLA Batteries)	24V (2x12V), 150Ah	
HYDRAULIC SYSTEM		
Hydraulic Oil Volume	2.25 gal	8.5 L
WEIGHT		
Machine Weight	4,365 lb	1,980 kg



ANSI A92.20, CSA B354.6
 Please contact LGMG for more details. LGMG reserves the right to change technical data without prior notice.
 All photos and pictures in this brochure are for promotional purposes only.
 This brochure comes into effect in December, 2025.

LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States
 Email: sales@lgmgna.com Tel: +1 833 288 5464

www.lgmgna.com

