


Service Doors Rolling Doors



6266 shown in stainless steel #4 finish and outside mounted.

VERSATILE AND TOUGH.

C.H.I. rolling service doors are engineered and designed for the toughest of environments. Rolling doors are built to provide a high degree of confidence for specifiers and end users for a wide variety of unique applications. Choose from slat profiles, gauges, mounting options, material, and color options to customize the door to fit your building's needs.



BEST MARKET USES

Industrial • Grain Elevators • Exterior Mounted Doors •
Parking • High Security • Non-Insulated Storage • Large Openings

MODEL SELECTION CHART

	Model	Slat Profile	Slat Material	Gauge	Insulation / R-Value ³	Max. Size ²	Colors ¹ / Finishes ¹
Curved Slat	6180	C2.6	Steel	18 Gauge	Non-Insulated	30'0" x 28'0"	Gray, White, PC
	6200			20 Gauge		28'4" x 28'0"	Gray, White, Galvanized, PC
	6220			22 Gauge		20'4" x 20'4"	Gray, White, Tan, Brown, Galvanized, PC
Flat Slat Non-Insulated	6181	F2.5	Steel	18 Gauge	Non-Insulated	30'0" x 28'0"	Gray, White, PC
	6201			20 Gauge		28'4" x 28'0"	Gray, White, Galvanized, PC
	6221			22 Gauge		20'4" x 20'4"	Gray, White, Tan, Brown, Galvanized, PC
	6241	24 Gauge	12'0" x 14'4"				
	6244	F2.7	Aluminum	16 Gauge [.050]		14'4" x 18'4"	Clear Anodized
	6266		Stainless Steel	22 Gauge		18'4" x 20'4"	#4 Finish
Flat Slat Insulated	6182	F2.5	Steel	Front: 18 Gauge Back: 24 Gauge	Polystyrene / R-4.7	30'0" x 24'0"	Front: Gray, White, PC Back: Gray, White, Tan, Brown, Galvanized, PC
	6202	F2.7		Front: 20 Gauge Back: 24 Gauge	Polyurethane / R-7.2	30'0" x 24'0"	Front: Gray, White, Galvanized, PC Back: Gray, White, Tan, Brown, Glvanized, PC
	6222			Front: 22 Gauge Back: 24 Gauge		24'4" x 20'4"	Front/Back: Gray, White, Tan, Brown, Glvanized, PC
	6242			Front: 24 Gauge Back: 24 Gauge		24'4" x 16'4"	

¹ Refer to your local Dealer for exact color or finish match. ² Sizes displayed as width x height. Consult factory for larger sizes. ³ R-values have been calculated in accordance with ASTM C518 standards.

PC = doors available in 188 powder coated options.

CURTAIN PROFILES



Curved [C2.6]



Flat [F2.5]



Flat [F2.5] - Polystyrene



Flat [F2.5] - Perforated



Flat [F2.5] - Fenestrated




Flat [F2.7]




Flat [F2.7] - Polyurethane


MOUNTING OPTIONS Interior/Exterior



Steel



Wood



Masonry

OPERATION

LiftMaster® commercial door operators will keep your rolling door in operation safely and efficiently so your business can keep running smoothly. Rolling Doors can be specified for manual, chain, or motor operation based on size requirements.



H



GH

LiftMaster®