




D806



- The small pieces of middle lateral patterns offer good braking, driving and grip performance
- The design of the closed shoulder pattern offers good wear resistance and balance abrasion
- Excellent comprehensive performance comes from special formula of low thermogenesis and good wear resistance
- Suitable for all wheels position and adapting to a variety of roads and complex driving conditions

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	20	279	1054	850	123	3000	2725
11R24.5	16	8.25	20	279	1104	850	123	3250	3000
295/75R22.5	16	9.00	20	298	1014	830	120	3000	2725

D816




- This tire has good performance of draining and driving and it also has excellent wear-resistance, driving power and braking ability
- It has marvelous braking ability,turning ability and safety assurance
- It has great performance of sideslip and slippery resistance and also the good performance of effective noise reduction and better heat dispersion
- The tire owns great performance of the adhesion to the ground, Which is not losing the carrying capability and can also keep the high speed ability

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	16.5	279	1054	850	123	3000	2725

QUINGDAO TIRE INTERNATIONAL GROUP LLC

D826



- Non-directional deep tread pattern for muddy and soft surfaces
- The features are extra-long life, superior cut resistance and excellent traction
- Applicable to earthmoving vehicles,such as rear and bottom dump trucks

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	20	279	1054	850	123	3000	2725
11R22.5	18	8.25	20	279	1104	850	123	3250	3000
11R24.5	16	9.00	20	298	1014	830	120	3000	2725

D856



- Wider tread,ensure driving safety
- Better structure,ensure the safety and longer mileage
- Special design,ensure heat radiation and durability
- Superior irregular wear resistance

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18	9.0	19.5	300	1086	930	135	3550	3250
295/80R22.5	18	9.0	19.5	240	1048	900	131	3550	3250

QUINGDAO TIRE INTERNATIONAL GROUP LLC

D866



- Close shoulder designs, the block pattern offe excellent drive force and good braking performance on paved road condition
- Excellent load capacity, Longer mileage, Super Durability

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
315/80R22.5	20	9.0	20	312	1076	850	123	4000	3350

S116



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handling
- The tiny deep-groove pattern design of the side of the tread that can improve the ability of avoiding partial grinding
- Suitable for steer or all wheel position of heavy truck running on high-grade road
- This tire can be used to the guiding wheel position and all other wheel positions of the heavy truck for middle and long distance in all good condition road

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	850	123	3000	2725
11R22.5	18	8.25	14.5	279	1054	850	123	3000	2725

QUINGDAO TIRE INTERNATIONAL GROUP LLC

S126



- Wide tread design ensure excellent wear-resistance
- It has four-line fore-and-aft sagittal groove design that can effectively avoid sideslip and offer good performance of handling
- The tiny deep-groove pattern design of the side of the tread that can improve the ability of avoiding partial grinding
- The brand-new tire shoulder low heat generation compound offers excellent high-speed performance
- Suitable for all wheel position of heavy truck running on high-grade road. Special formula design of tread offer better heat dispersion and more comfortable and safe driving experience

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	850	123	3000	2725
11R22.5	18	8.25	14.5	279	1054	850	123	3250	3000
11R24.5	16	8.25	14.5	279	1104	830	120	3250	3000
295/75R22.5	16	9.00	14.5	298	1014	830	120	3000	2725
295/80R22.5	18	9.00	15.5	230	1040	900	131	3550	3250
385/65R22.5	20	11.75	15.5	389	1072	900	131	4500	4500

S136



- Classic pattern with three groove design ensure small rolling and low heat generation
- Ensure driving comfortable and safety during operation
- Low running noise
- The tire makes a little noise
- Suitable for bus or light truck running on high-grade road or highway

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
11R22.5	16	8.25	14.5	279	1054	850	123	3000	2725
11R22.5	18	8.25	14.5	279	1054	850	123	3250	3000
11R24.5	16	8.25	14.5	279	1104	830	120	3250	3000
12R22.5	18	9.00	16.5	300	1084	930	135	3550	3250
13R22.5	20	9.75	15.3	320	1124	830	120	4000	3650
315/80R22.5	20	9.00	13.3	312	1076	850	123	4000	3350

QUINGDAO TIRE INTERNATIONAL GROUP LLC

S166



- Outstanding self-cleaning tread design promote adaptability in long haul road conditions
- High density, flexomatic blading,for outstanding braking on wet surfaces combined with high mileage
- More mileage and greater lateral stability

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
295/80R22.5	18	9.0	16	298	1044	900	131	3550	3450

S176



- New designed pattern, suitable for well paved road condition with high speed level and excellent durability
- Tread rubber compound for fine drainage and grip performance which improved outstandingly
- Heavy loading capacity, low heat build-up, high speed and low noise

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
12R22.5	18	9.0	15	300	1085	930	135	3550	3250

S196



- New designed pattern, suitable for well paved roadcondition with high speed level and excellent durability
- Tread rubber compound for fine drainage and grip performance which improved outstandingly
- Heavy loading capacity, low heat build-up, high speed and low noise

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		A.P.		MAXIMUM LOAD (kg)	
				SECTION WIDTH	OVERALL DIAMETER	KPA	PSI	SINGLE-TYRE	DOUBLE-TYRE
??? 315/80R22.5	20	9.0	16.5	312	1076	850	123	4000	3350

QUINGDAO TIRE INTERNATIONAL GROUP LLC

T616



- Excellent anti-damage ability can undertake complex road conditions
- Fit for trailer axle of truck and suitable for complex road conditions
- High strength tyre carcass is suitable for retreading
- Specialized wear-resistant and anti-stab formula

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		INFLATION PRESSURE (kpa)	MAXIMUM LOAD (kg)
				SECTION WIDTH	OVERALL DIAMETER		
385/65R22.5	20	11.75	15.5	389	1072	900	4500

T626



- Suitable for all wheels position of both truck and bus working on complex roads in all-weather conditions
- Low rolling resistance, low heat resistance, fuel economy, and excellent guiding performance
- Wide base section design offers superior safety and ride comfort
- Super wear-resistant formula design for medium and long distance provides excellent mileage

TYRE SIZE	PLY RATING	RIM	TREAD DEPTH (mm)	NEW TYRE INFLATION DIMENSION (mm)		INFLATION PRESSURE (kpa)	MAXIMUM LOAD (kg)
				SECTION WIDTH	OVERALL DIAMETER		
385/65R22.5	20	11.75	15.5	389	1072	900	4500

QUINGDAO TIRE INTERNATIONAL GROUP LLC