

Standard Wide Stile Entrances

Our Standard Wide Stile Entrances are designed for moderate to heavy use in commercial applications. Standard Wide Stile has 5" (127mm) vertical stiles and top rail, and 6-1/2" (165mm) bottom rail – optional up to 10" for ADA compliance. "Stacked" bottom rails beyond 10" also available. The smooth design of Tubelite's door hardware features a convenient pull handle and push bar with lock location 36" above the finished floor. Stock doors and frames are anodized with clear, dark bronze or black and readily available for quick delivery.

Our doors come with newly designed "blade" style glass stops as well as built-in glass jacks which aid in squaring up the doors in relation to the frames.

Durable Tie-Rod Construction

The strength and flexibility of steel tie-rod construction is what holds it all together and makes our doors endure. Tie-rod assembly is as durable as welded corner construction, but superior in many ways. Tubelite doors can be modified, disassembled or resized right in the field. No other door offers you this much strength and flexibility.



**400 Series
Curtainwall**



**ALSO
USED
WITH**

**14000 Series
Storefront**

TUBELITE®
DEPENDABLE

LEADERS IN ECO-EFFICIENT STOREFRONT,
CURTAINWALL AND ENTRANCE SYSTEMS

Standard Wide Stile Entrances



System Features:

- Standard 5" (127mm) sight line on verticals and top rail
- Deadbolt lock
- 1" dia. push bar and offset pull handle
- Standard infill options 1" (25.4mm), and 1/4" (6.35mm), other infills available
- 3'0" width single doors, 6'0" width pairs of doors
- 7'0" height door leaves*

**available up to 10' with engineering review*

Optional Features:

- 6-1/2" (165mm) and 10" (254mm) bottom rails
- Mortised butt hinges, offset pivots, continuous hinges, center pivots
- Latch locks, cvr & rim panics, electric strikes
- Hardware by others
- 1-3/4" or 2" x 4-1/2" sight line frame member
- Intermediate horizontal or vertical mid-rails
- A wide variety of standard anodized and painted colors are available to complement any project with warrantied protection, as well as street appeal.
- Custom height and width doors

Note: Dimensions do not include glass stops.	
Standard Entrance Series	Wide Stile
Traffic	Heavy
Vertical Stile 1-3/4" x	5" (127mm)
Top Rail 1-3/4" x	5" (127mm)
Bottom Rail 1-3/4" x	6-1/2" (165mm) (opt. up to 10")*

***"stacked" bottom rail options above 10" also available*

Standard Wide Series Product Specifications

Application: Public Buildings

Description: 5" vertical stiles and top rail, and 6-1/2" bottom rail – optional up to 10" for ADA compliance

Glass:	Air Infiltration:	Structural:	CRF - Single Door:
1" std (1/8" – 1")	1.0 CFM / Ft.2 @ 1.57 PSF	30 PSF – Design 45 PSF – Overload	CRFf = 28 CRFg = 24 Overall = 24

****** U-Factor per NFRC 100: Refer to the U-Factor table at: www.tubeliteusa.com/products/entrances/standard-wide/ for other glass makeups and configurations.

DISCLAIMER: Tubelite takes no responsibility for product selection or application, including, but not limited to, compliance with building codes, safety codes, laws, merchantability or fitness for a particular purpose; and further disclaims all liability for the use, in whole or in part, of this Technical Guide in preparation of project specifications and/or other documents. Technical Guides are subject to change at any time, without notice, and at Tubelite's sole discretion. ©2024 Tubelite

090324