

A

Hinges & Pivots

B

Pulls & Plates

C

Flush Bolts & Coordinators

D

Latches, Catches & Bolts

E

Stops

F10

Exterior Hardware

G

Miscellaneous Hardware



Meets ANSI/BHMA A156.16, L12231,

25 Screen Door Pull

- Cast aluminum or epoxy-coated aluminum
- Also used as a window lift, drawer or utility pull

Dimensions

Length 4-7/8"

Projection 1-5/32"

Mounting holes 4-1/8" center to center

Finishes

Ives Number	A3	A92	A-W	A-B
BHMA	666	673		

CS115 Crash Stop

- Specially designed for full-size exterior doors.
- Tear resistant, grey vinyl cover.
- Heavy duty compression spring assembled to both ends of chain and end brackets.
- Packed with sheet metal screws.
- Cast Brass brackets with solid, welded steel chain.
- Optional sex bolt mounting available in US26D (626) only.



Meets ANSI/BHMA A156.16, L12231,

Dimensions

Bracket Size: 1-9/16" x 1-9/16"

Available Lengths:

20-1/2" — Recommended for 30" Door Width (Product No. CS115-20)

25-1/2" — Recommended for 36" Door Width (Product No. CS115-25)

30-1/2" — Recommended for 42" Door Width (Product No. CS115-30)

Finishes

Ives Number	US10B	US26D
BHMA	613	626