

# SUPERTRAC TRAILER AXLES



## SuperTrac STANDARD

The SuperTrac Standard is a straight 5" round axle with nominal 1/2" wall or 5/8" wall & 16½"x7" brakes. These axles are fully dressed with tapered spindles, 30/30 brake chambers, 5.5" auto-slacks, & R20 brake lining. (71.5 & 77.5" Tracks)

## SuperTrac LOWBOY

The SuperTrac Lowboy is a straight 5" round axles with nominal 3/4" wall & 16½"x7" brakes. These axles are fully dressed with tapered spindles, 30/30 brake chambers, 5.5" auto-slacks, & R23 brake lining. (76.5 & 77.5" Tracks)

## SuperTrac TAG

The SuperTrac Tag is a straight 5" round axles with nominal 5/8" wall & 12¼"x7½" brakes. These axles are fully dressed with tapered spindles, 30/30 brake chambers, curved auto-slacks, & R23 brake lining. (71.5 & 77.5" Tracks)

## SuperTrac WHEEL ENDS

The SuperTrac wheel ends have extended service brakes, lubricated with oil, Stemco hubcap & Guardian Seals, hub piloted cast hub & drum, long studs with all wheel nuts, and all with a 1 year limited warranty. SuperTrac wheel ends offered as ABS or Non-ABS. Non-ABS axles are without sensor but with ABS tone rings installed.



cushcorp.com | 877.789.6247