

# Oxford® Tumbled Texture 6cm



Product	Pieces / Sq. Ft. Per Layer / Pallet	Layers / Sq. Ft. Per Pallet	Weight Per Pallet / Sq. Ft.
Oxford Tumbled Square <i>sold by the layer</i>	13.44 sq. ft. per layer 64 pcs./layer	8 layers/pallet = 107.52 sq. ft.	2,944 lbs./pallet 27.4 lbs./sq. ft.
Oxford Tumbled Rectangle <i>sold by the layer</i>	12.6 sq. ft. per layer 40 pcs./layer	8 layers/pallet = 100.8 sq. ft.	2,773 lbs./pallet 27.5 lbs./sq. ft.

## APPEARANCE

Edge Detail - Pillow Top/Rounded  
 Surface Texture - Smooth  
 Joint Spacing - 2.2 mm

## TECHNOLOGIES

Face Texture - Standard Finish

## TECHNICAL INFORMATION

Conforms to ASTM C936  
 Eligible for LEED v4.1 credits


## APPLICATIONS

Pedestrian  
 Residential Vehicular


## INSTALLATION METHODS

Hand

## PATTERNS



MUSTER D



MUSTER K



CIMARRON



GREY QUARTZ



PEWTER



RIVERSIDE



SQUARE  
 (H) 2 3/8" x (D) 5 1/2" x (L) 5 1/2"



RECTANGLE  
 (H) 2 3/8" x (D) 5 1/2" x (L) 8 1/4"

Reading Rock recommends using a roller compactor on PaverLock Elite pavers.

