


TEAR TAPE 26 MICRON MOPP Specification Sheet

PRODUCT DESCRIPTION

This product is available in tape widths ranging from 1.6mm - 20mm at lengths of up to 120km and can be wound onto a choice of cores including 29mm, 76mm, 82.5mm and 152mm internal diameter. Other core sizes are available on request.



PROPERTY	TEST METHOD	UNITS	SPECIFICATION
Tape width tolerance	Internal method	mm	± 0.1
Film thickness	AFERA 5006	µm	26 ± 2
Total tape thickness	AFERA 5006	µm	37 ± 5
Breaking strength	AFERA 5004	kgf/25mm	≥24
Elongation at break	AFERA 5004	%	≥15
Tensile strength at break	AFERA 5004	kgf/mm ²	≥40
Tensile modulus at 10% elongation	Internal method	kgf/mm ²	≥200
Peel adhesion to stainless steel	FINAT FTM 1	gf/25mm	≥400
Loop tack to glass	FINAT FTM 9	gf/25mm	≥400

Values quoted are based upon tests we believe to be reliable.

The values are intended as a source of information and are given without guarantees and do not constitute a warranty.

Prior to use, purchasers should independently determine the suitability of any product for a specific purpose.

FURTHER INFORMATION

All products are traverse wound with the adhesive on the inside.

All joints are transparent butt joints which are designed to unwind without the tape breaking.

Revisione	Data	Redazione	Approvazione	Pag.
1	24.01.2021	Lazarini Gianpaolo	Froldi Carol	1 / 1