



Firewall Rules - Revised 2024

- **SIP ALG needs to be DISABLED**
 - **Make sure that NAT timeout or UDP timeout is set to 60 seconds**
-

IP Blocks:

- 64.94.196.0/23
- 198.58.40.0/21
- 206.166.216.0/22

Ports Required for LPS Services:

- SIP Ports: 5060 – 5080
- RTP Ports: 10000 - 65353 UDP

Provisioning Server IPs:

- 184.169.138.90
- 23.21.130.170
- 23.23.252.206
- 23.23.89.246
- 54.234.135.90
- 54.208.136.177

Ports Used for Provisioning:

- FTP: 21; 1024 - 1536 TCP (Passive FTP)
- HTTP: 80 TCP
- HTTPS: 443 TCP
- HTTP: 8080 TCP
- HTTPS: 8443 TCP

Whitelist The Following IPs And Emails If Using Hosted Fax Products:

- 216.187.65.178
- 216.187.65.179
- 168.75.50.130
- 168.75.50.131
- 35.227.166.44

- 4.53.194.121
- 4.53.194.122
- messages@receive.faxhd.com
- no-reply@notifications.faxhd.com

SMTP Email Settings for Send and Receive:

- 206.166.216.90
- 206.166.218.192
- 206.166.219.42
- 206.166.217.153
- 206.166.216.218
- 206.166.218.133
- 204.236.248.254