

MODELO	ACABADO	ABERTURA DEL ROMBO				CALIBRE NOMINAL	ESPESOR		SECCION		PESO APROX. Kg/Mi2	DIMENSION DE LA HOJA	
		LCR		LLR			Palg.	mm.	Palg.	mm.		Acho, Mi.	Largo, Mi.
		Palg.	mm.	Palg.	mm.								
1/4"#20	MR	0.25	6.4	1.00	25.4	20	0.036	0.91	0.072	1.8	4.20	0.91, 1.22	2.44, 3.05
1/4"#20	PR	0.27	7.0	1.00	25.4	20	0.036	0.91	0.079	2.0	3.85	0.91, 1.22	2.44, 3.05
1/4"#18	MR	0.25	6.4	1.00	25.4	18	0.047	1.20	0.072	1.8	5.60	0.91, 1.22	2.44, 3.05
1/4"#18	PR	0.27	7.0	1.00	25.4	18	0.047	1.20	0.079	2.0	5.10	0.91, 1.22	2.44, 3.05
1/2"#20	MR	0.50	13.0	1.20	30.5	20	0.036	0.91	0.072	1.8	2.10	0.91, 1.22	2.44, 3.05
1/2"#20	PR	0.55	14.0	1.20	30.5	20	0.036	0.91	0.079	2.0	1.90	0.91, 1.22	2.44, 3.05
1/2"#18	MR	0.50	13.0	1.20	30.5	18	0.047	1.20	0.088	2.2	3.40	0.91, 1.22	2.44, 3.05
1/2"#18	PR	0.55	14.0	1.20	30.5	18	0.047	1.20	0.094	2.4	3.10	0.91, 1.22	2.44, 3.05
1/2"#16	MR	0.50	13.0	1.20	30.5	16	0.060	1.52	0.088	2.2	4.30	0.91, 1.22	2.44, 3.05
1/2"#16	PR	0.55	14.0	1.20	30.5	16	0.060	1.52	0.094	2.4	4.00	0.91, 1.22	2.44, 3.05
1/2"#13	MR	0.50	13.0	1.20	30.5	13	0.092	2.34	0.096	2.4	7.20	0.91, 1.22	2.44, 3.05
1/2"#13	PR	0.55	14.0	1.20	30.5	13	0.092	2.34	0.102	2.6	6.60	0.91, 1.22	2.44, 3.05
3/4"#16	MR	1.00	25.4	2.00	50.8	16	0.060	1.52	0.099	2.4	2.60	0.91, 1.22	2.44, 3.05
3/4"#16	PR	1.10	27.9	2.00	50.8	16	0.060	1.52	0.102	2.6	2.40	0.91, 1.22	2.44, 3.05
3/4"#13	MR	1.00	25.4	2.00	50.8	13	0.092	2.34	0.096	2.4	3.90	0.91, 1.22	2.44, 3.05
3/4"#13	PR	1.10	27.9	2.00	50.8	13	0.092	2.34	0.102	2.6	3.60	0.91, 1.22	2.44, 3.05
3/4"#10 (13)	MR	1.00	25.4	2.00	50.8	13	0.092	2.34	0.144	3.6	5.90	0.91, 1.22	2.44, 3.05
3/4"#10 (13)	PR	1.10	27.9	2.00	50.8	13	0.092	2.34	0.153	3.9	5.40	0.91, 1.22	2.44, 3.05
3/4"#9 (10)	MR	1.00	25.4	2.00	50.8	10	0.133	3.40	0.148	3.7	8.80	0.91, 1.22, 1.52	2.44, 3.05
3/4"#9 (10)	PR	1.10	27.9	2.00	50.8	10	0.133	3.40	0.157	4.0	8.00	0.91, 1.22, 1.52	2.44, 3.05
1" # 16	MR	1.10	28.0	2.40	60.0	16	0.062	1.52	0.096	2.4	2.10	0.91, 1.22	2.44, 3.05
1" # 16	PR	1.20	30.5	2.40	60.0	16	0.062	1.52	0.102	2.6	1.95	0.91, 1.22	2.44, 3.05
1" # 14	MR	1.10	28.0	2.40	60.0	14	0.075	1.90	0.122	3.1	3.20	0.91, 1.22	2.44, 3.05
1" # 14	PR	1.20	30.5	2.40	60.0	16	0.075	1.90	0.130	3.3	2.90	0.91, 1.22	2.44, 3.05
1" # 10	MR	1.10	28.0	2.40	60.0	10	0.133	3.40	0.155	3.9	7.10	0.91, 1.22	2.44, 3.05
1" # 10	PR	1.20	30.5	2.40	60.0	10	0.133	3.40	0.160	4.0	6.50	0.91, 1.22	2.44, 3.05
1" # 6	MR	1.10	28.0	2.40	60.0	6	0.187	4.76	0.275	7.0	17.40	0.91, 1.22	2.44, 3.05
1 1/2" # 16	MR	1.33	34.0	3.00	76.0	16	0.052	1.52	0.107	2.7	2.00	0.91, 1.22	2.44, 3.05
1 1/2" # 16	PR	1.45	36.5	3.00	76.0	16	0.052	1.52	0.110	2.8	1.85	0.91, 1.22	2.44, 3.05
1 1/2" # 13	MR	1.33	34.0	3.00	76.0	13	0.092	2.34	0.104	2.6	2.90	0.91, 1.22	2.44, 3.05
1 1/2" # 13	PR	1.45	36.5	3.00	76.0	13	0.092	2.34	0.110	2.8	1.85	0.91, 1.22	2.44, 3.05
1 1/2"# 10 (13)	MR	1.33	34.0	3.00	76.0	13	0.092	2.34	0.137	3.4	3.90	0.91, 1.22	2.44, 3.05
1 1/2"#10 (13)	PR	1.45	36.5	3.00	76.0	13	0.092	2.34	0.145	3.7	3.60	0.91, 1.22	2.44, 3.05
1 1/2"#9 (10)	MR	1.33	34.0	3.00	76.0	10	0.133	3.40	0.142	3.6	5.90	0.91, 1.22	2.44, 3.05
1 1/2"#9 (10)	PR	1.45	36.5	3.00	76.0	10	0.133	3.40	0.150	3.8	5.40	0.91, 1.22	2.44, 3.05
1 1/2"#6	MR	1.33	34.0	3.00	76.0	6	0.188	4.76	0.201	5.1	11.40	0.91, 1.22	2.44, 3.05
2"# 10 (13)	MR	1.85	47.0	4.00	101.6	13	0.092	2.34	0.164	4.1	3.30	0.91, 1.22	2.44, 3.05