



The Luxury Range of Air Conditioning

KYR-25CO/LUX
9000BTU COOL ONLY

KYR-35GW/LUX
12000BTU HEAT & CO

KYR-45GW/LUX
14000BTU HEAT & CO

KYR-55GW/LUX
18000BTU HEAT & CO

R290
REFRIGERANT



STERILISATION INSIDE
UV-C
DESTROYS AIRBORNE
VIRUSES AND BACTERIA



The All New LUX Air range of Portable Air Conditioning Units features market leading technology, with the ability to Sanitize the air in the room whilst cooling or heating!



- R290 Refrigerant - Eco Friendly
- UV-C Sterilisation - High Output UV-C kills Viruses
- Wi-Fi Controllable with Tuya Smart Life Application
- Amazon Alexa & Google Assistant Voice Compatible
- A Energy Efficiency Rating (Heating and Cooling)
- SLEEP Mode - Quiet Operation for Easy Sleeping
- 12 Hour Timer Function
- Infrared Remote Control

KYR-25CO/LUX
KYR-35GW/LUX
KYR-45GW/LUX



KYR-55GW/LUX

Please note, we do not supply the 18,000 BTU model



WORKS WITH
amazon alexa

works with the
Google Assistant

UV-C
STERILISATION
INSIDE

Remote Control
Included with
Every Unit

Smart Life APP

R290
REFRIGERANT

Accessories Included

- Exhaust Hose
- Unit to Hose Adaptor
- Window Slider
- Window to Hose Adaptor
- Remote Control
- Condensate Drain Tube
- User Manual
- Warranty Card

*Exhaust Hose Extension Kits Sold Separately

Product Code	KYR-25CO/LUX	KYR-35GW/LUX	KYR-45GW/LUX	KYR-55GW/LUX
EAN Barcode	5060974530434	5060974530441	5060974530458	5060974530465
Energy Efficiency Rating (Cooling)	A	A	A	A
Energy Efficiency Rating (Heating)	COOL ONLY	A	A	A
Power Rating (Ph/V/Hz)	1/220-240V/50Hz	1/220-240V/50Hz	1/220-240V/50Hz	1/220-240V/50Hz
Cooling Capacity (BTU/hr)	9,000 (2.6kW)	12,000 (3.5kW)	14,000 (4.1kW)	18,000 (5.2kW)
Heating Capacity (BTU/hr)	COOL ONLY	12,700 (3.7kW)	16,000 (4.6kW)	19,000 (5.6kW)
Power Input W (Cooling/Heating)	1000	1350/1391	1538/1520	2000/2043
Current Input A (Cooling/Heating)	4.2	5.5 / 6.0	8.4 / 8.5	8.4 / 8.5
EER (BTU/hr.w)	2.9	2.6	2.3	2.6
COP (w/w)	N/A	2.3	3.0	2.9
Refrigerant Type	R290	R290	R290	R290
Compressor Brand	Toshiba	Toshiba	Toshiba	Toshiba
Dehumidification (L/hr)	1.0	1.2	1.5	1.8
Noise dB(A)	56	56	56	65
Airflow (m3/hr)	330	380	380	450
Fan Speeds	3	3	3	3
Recommended Room Size (m2)	30m sq	35m sq	40m sq	45m sq
Max Conservatory Size (m2)	15m sq	20m sq	23m sq	25m sq
Net/ Gross Weight (kg)	28 / 31	30 / 33	31 / 34	37 / 42
Net Dimension (mm) WxDxH	410x330x710	410x330x710	410x330x710	440x370x756
Gross Dimension (mm) WxDxH	477x380x875	477x380x875	477x380x875	630x412x882
Exhaust Hose Diameter (mm)	150	150	150	160
Exhaust Hose Length (m)	1.5	1.5	1.5	1.5
UV-C Lamp Voltage	12V DC	12V DC	12V DC	12V DC
UV-C Lamp Wattage	0.48W	0.48W	0.48W	0.48W
WiFi Control	Yes	Yes	Yes	Yes

Please note portable air conditioning units are NOT designed to be run for 24 hours a day. These are NOT designed for server/ IT room cooling.

Please note, we do not supply the 18,000 BTU model

boilersupermarket 