



INDUSTRIAL KINETICS, INC.

TOTAL MATERIAL HANDLING SYSTEMS

2535 Curtiss Street Downers Grove IL 60515 Phone: 630-655-0300 Fax: 630-655-1720

BAG INFEED CONVEYOR

STANDARD FEATURES

- 10' Long with heavy duty 4 gauge (approximately ¼") steel frame
- Two drive – belt and roller sections
- PVC Belt section 6' long with 18" wide belt
- High speed roller section 4' long
 - 1.9" Diameter rollers on 3" centers
 - Notched conveyor frame
 - Conveyor roller bearings are ABEC-1
- Fixed bolt on end stop
- Adjustable pre-galvanized floor supports



PICTURED ABOVE WITH OPTIONAL DRUM STYLE BAG HEIGHT LIMITER

STANDARD OPTIONS

- 8' Long conveyor, 4' belt and 4' roller
- Bag drum height limiter
- 24" Wide belt, 28" Conveyor
- Removable end stop – pins
- Air cylinder driven end stop
- Standard shaft mount belt section speeds (at 60 Hz)
 - 52, 69, 82, 103, 137, 206 FPM
- Standard roller section speeds (bold are most popular, at 60 Hz)
 - 96, 101, 107, 118, 122, 131, 137, 143, 152, **161**, 175, 184, 197, **206** FPM

PLEASE CONTACT THE FACTORY FOR APPLICATION ASSISTANCE.

SPECIFICATIONS SUBJECT TO CHANGE, WE OFTEN CUSTOMIZE TO THE APPLICATION