

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Issue date: 11/18/2015 Revision date: 3/15/2022 Supersedes: 5/27/2019 Version: 2.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Fuel Right Winter 3K
Product code : W3K0222

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Fuel additive

1.3. Supplier

Manufacturer

Fuel Right
41 Germay Drive
Wilmington, Delaware 19804 - USA
T 302-425-4400

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flam. Liq. 4	Combustible liquid
Skin Irrit. 2	Causes skin irritation
Eye Dam. 1	Causes serious eye damage
Carc. 2	Suspected of causing cancer
Repr. 2	Suspected of damaging fertility or the unborn child
STOT RE 2	May cause damage to organs through prolonged or repeated exposure
Asp. Tox. 1	May be fatal if swallowed and enters airways

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Combustible liquid
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye damage
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
If exposed or concerned: Get medical advice/attention.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Petroleum distillates, hydrotreated light	CAS-No.: 64742-47-8	50 – 60
Solvent naphtha, petroleum, heavy aromatic	CAS-No.: 64742-94-5	15 – 30
Dipropylene glycol monomethyl ether	CAS-No.: 34590-94-8	10 – 15
Cyclic amino compound	Trade Secret	5 – 10
Aliphatic Diamine	Trade Secret	< 5
Naphthalene	CAS-No.: 91-20-3	< 5
Hexanoic acid, 2-ethyl-, ethenyl ester	CAS-No.: 94-04-2	< 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms : Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water fog. Dry chemical. Alcohol-resistant foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen. irritating vapors.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation. Spilled material may present a slipping hazard.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid contact with skin and clothing. Do not get in eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.

Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Store locked up. Keep away from heat and direct sunlight. Store tightly closed in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fuel Right Winter 3K	
No additional information available	
Petroleum distillates, hydrotreated light (64742-47-8)	
No additional information available	
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
No additional information available	
Dipropylene glycol monomethyl ether (34590-94-8)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	600 mg/m ³
OSHA PEL (TWA) [2]	100 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Cyclic amino compound (Trade Secret)	
No additional information available	

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Aliphatic Diamine (Trade Secret)	
No additional information available	
Naphthalene (91-20-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	10 ppm
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	Parameter: 1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis - Sampling time: end of shift (nonquantitative, nonspecific)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [1]	50 mg/m ³
OSHA PEL (TWA) [2]	10 ppm
Hexanoic acid, 2-ethyl-, ethenyl ester (94-04-2)	
No additional information available	

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration
Eye protection:
Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : No data available.
- Color : Hazy pale yellow to light amber
- Odor : Hydrocarbon / Fish oil / Ammonia
- Odor threshold : No data available

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 74 °C / 165.2 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Combustible liquid.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Open flame.

10.5. Incompatible materials

Oxidizers.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of nitrogen. irritating vapors. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Petroleum distillates, hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 590 mg/m ³ (Exposure time: 4 h)
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg
LD50 dermal rabbit	9500 mg/kg
Naphthalene (91-20-3)	
LD50 oral rat	1110 mg/kg
LD50 dermal rabbit	1120 mg/kg
LC50 inhalation rat	> 0.4 mg/l/4h
Hexanoic acid, 2-ethyl-, ethenyl ester (94-04-2)	
LD50 oral rat	4290 mg/kg
LD50 dermal rabbit	> 16 ml/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen, Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
NOAEL (animal/male, F0/P)	35 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test
NOAEL (animal/female, F0/P)	125 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:OPPTS 870.3650 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test
Naphthalene (91-20-3)	
LOAEL (animal/female, F0/P)	50 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Naphthalene (91-20-3)	
LOAEL (animal/female, F1)	450 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)
NOAEL (animal/female, F0/P)	120 mg/kg body weight Animal: rabbit, Animal sex: female, Guideline: other:OECD Guideline 414 (Prenatal Developmental Toxicity Study)

STOT-single exposure : Not classified
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Petroleum distillates, hydrotreated light (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg body weight Animal: rat, Animal sex: female
NOAEC (inhalation, rat, vapor, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LOAEL (oral, rat, 90 days)	1250 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	200 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
LOAEC (inhalation, rat, vapor, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	625 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	2000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, vapor, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity: 90-Day Study)

Dipropylene glycol monomethyl ether (34590-94-8)	
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: other:KANPOGYO No.700, YAKUHATSU No. 1039.61, and KIKYKU No. 1014.
NOAEL (dermal, rat/rabbit, 90 days)	2850 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Naphthalene (91-20-3)	
LOAEL (oral, rat, 90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
LOAEC (inhalation, rat, vapor, 90 days)	0.011 mg/l air Animal: rat, Guideline: EPA OPP 82-4 (90-Day Inhalation Toxicity), Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral, rat, 90 days)	200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Hexanoic acid, 2-ethyl-, ethenyl ester (94-04-2)	
NOAEL (oral, rat, 90 days)	200 mg/kg body weight Animal: rat

Aspiration hazard : May be fatal if swallowed and enters airways.
Viscosity, kinematic : No data available
Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotreated light (64742-47-8)

LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)

LC50 - Fish [1]	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [2]	0.76 mg/l Test organisms (species): Daphnia magna

Dipropylene glycol monomethyl ether (34590-94-8)

LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea: Acartia tonsa
LOEC (chronic)	0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
NOEC (chronic)	≥ 0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

Naphthalene (91-20-3)

LC50 - Fish [1]	5.74 – 6.44 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	2.16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	1.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [2]	1.96 mg/l (Exposure time: 48 h - Species: Daphnia magna [Flow through])
NOEC (chronic)	0.59 mg/l Test organisms (species): Daphnia pulex Duration: '125 d'
NOEC chronic fish	≈ 0.37 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'

Hexanoic acid, 2-ethyl-, ethenyl ester (94-04-2)

LC50 - Fish [1]	0.84 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	1.8 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

Fuel Right Winter 3K

Persistence and degradability	Not established.
-------------------------------	------------------

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.3. Bioaccumulative potential

Fuel Right Winter 3K	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF - Fish [1]	61 – 159
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
BCF - Fish [1]	61 – 159
Partition coefficient n-octanol/water	2.9 – 6.1
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water	-0.064 (at 20 °C)
Naphthalene (91-20-3)	
BCF - Fish [1]	30 – 430
Partition coefficient n-octanol/water	3.6

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapors are flammable.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not regulated for transport (non-bulk packages)

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information


15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 11/18/2015
Revision date : 03/15/2022
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of H-phrases	
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2

Indication of changes:
Composition/Information on ingredients. GHS classification.

Fuel Right Winter 3K

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.