



36MM EXTRUDED ROLLER SHUTTER

(High Security Commercial)



This roller shutter range is made with a precision extruded roller shutter profile, and is suitable for many commercial and industrial grade applications.

SUITABLE APPLICATIONS

- Commercial Windows.
- Commercial Shop Fronts & Doorways.
- Garage Doors.
- High Security for Factories, Warehouses, Clubs, Pubs & Hotels, Restaurants, Pharmacies, Sports Complexes, Arcades, Shopping Mall Entrances, Mining & High Security Areas.

FEATURES

- High quality, strong aluminium alloy construction.
- Commercial grade double wall extruded profile for heavy duty strength.
- High quality powder coated finish for maximum abrasion resistance.
- Double line grooved and slight curved face profile.
- Roll-tight design.
- Range of colours.
- Heavy duty steel axle with high quality internal sealed bearings.
- Suitable for widespan widths up to 5800mm.
- Can be manually operated or motorised.
- Made in Australia.

* CW Products recommends the use of Photo Safety Cells and a Safety Brake when installing automated roller shutters over openings and doorways. Especially when the roller shutter is not in full view of the operator (eg. when using a remote control or wall switch positioned away from the roller shutter and out of view). When using a wall switch, we recommend a spring return switch/deadman switch.

TECHNICAL SPECIFICATIONS

Maximum Shutter Width	5800mm (with Winged Slat Locks)
Maximum Shutter Height	3000mm
Maximum Surface Area	12m ²
Curtain Weight/Metre ²	7.5kg
Number Of Slats/Metre	28
Profile Slat Covering	36mm
Profile Slat Thickness	9.7mm
Axle Types	Octagonal Steel
Bottom Bar Dimensions	55mm x 8.5mm
Guide Dimensions	68mm x 25mm/14mm (Heavy Duty Guide)
Paint Finish	High Quality Powder Coat Finish

MADE TO MEASURE ROLLER SHUTTERS

PELMET SIZES & MAXIMUM SHUTTER HEIGHT STANDARD SLAT LOCKS

Pelmet Box Size	Max. No. Of Slats	Max. Shutter Height (Including Pelmet)	Axle Size
180mm	50	1800mm	60mm
205mm	56	2020mm	70mm
230mm	72	2600mm	70mm
250mm	90	3250mm*	70mm
250mm	85	3050mm*	101mm with adaptor
250mm	72	2590mm	130mm with adaptor

* Measurement exceeds recommended maximum shutter height. May be allowed if other technical specifications are met. Check with your local CW Products representative.

WINGED SLAT LOCKS

180mm	38	1350mm	60mm
205mm	46	1650mm	70mm
230mm	62	2300mm	70mm
250mm	72	2600mm	70mm
250mm	78	2800mm	101mm with adaptor
250mm	65	2350mm	130mm with adaptor

ROLLER SHUTTER COLOUR OPTIONS

Profiles	Pelmets/Side Frames/Guides/Bottom Bars
 Cream	 Cream
 Magnolia Cream	 Magnolia Cream
 Clear Beige	 Clear Beige
 White	 White
 Shale Grey	 Shale Grey
 Black	 Brown
 Monument	 Black
 Anodised Silver	 Monument
 Woodland Grey	 Woodland Grey

Powder coated options available
(additional charges apply)

CONTROL OPTIONS

Manual Options



Steel Cable Winder
(Up To 50Kg)



Spring Loaded
With Key Lock



Remote Control
With SolarSmart™
Plus Automation
12V Motor
(Up To 50Kg)

Motorised Options



PowerSmart™
Control System
With 12V Motor
(Up To 50Kg)*



Wall Switch
With 240V
Electric Motor




Remote Control
With 240V
Electric SIMU Hz
Motor

Motorised Options (continued)



Key Switch
With 240V
Electric Motor



Crank Handle
With 240V
Electric Manual
Override Motor



Remote Control
(Key Ring Transmitter)
With 240V
Electric Motor &
Multi-Function SIMU
RSA Hz Radio Receiver
& Control Unit

* When used in conjunction with an assist spring as per CW Products specifications.

To order please complete a **CW Products Made To Measure Roller Shutter Order Form**.