



Rigtrans' own range of Tool Boxes is designed, manufactured and certified to DNVGL-ST-E271 (DNV 2.7-1), EN12079 and ISO10855. DNV-GL certified sling sets can be supplied.

To make for efficient land based depot operation, all model types are fitted with fork lift pockets and all Tool Boxes can be multi stacked with their slings fitted. Internally, a range of lashing points is provided to suit varied types of cargo.

Top opening lids can either be of aluminium construction or steel with counter balanced springs allowing for ease of operation. Options include security systems, shelving and compartmentalisation.

Brief Specifications:

External dimensions:	2,064mm x 1,228mm x 1,140mm (high) 6'9" x 4'0" x 3'8"
Internal dimensions:	1,842mm x 1,015mm x 831mm (high) 6'0" x 3'3" x 2'8"
Cubic capacity:	1.55m ³ , 55ft ³
Tare weight:	850kgs, 1,870lbs.
Payload:	5,000kgs, 11,020lbs.
Maximum Gross Weight:	5,850kgs, 12,890lbs
Features:	Steel lid with lift assisted by three coil springs - one person operation
Internal fittings:	A wide range of cargo lashing points is provided
Certification:	DNVGL-ST-E271, EN12079, ISO10855

Due to continuous product development, all specifications are indicative. Individual container's dimensions may differ.



06TB-NRGU-250723.

Rigtrans Intermodal Limited

Registered Office: 20 Edenfield Gardens, Worcester Park, Surrey KT4 7DT
Registered in England No. 10519137

T +44 (0) 20 8330 6888
M +44 (0) 7836 695569
E sales@rigtrans.com
W rigtrans.com