6.4K CAPACITY SINGLE TURRET
Model #ECT20108



General:	GVWR:	10,000 lbs.
	GAWR:	5,000 lbs. (per axle)
	Estimated Empty Weight:	3,600 lbs.
	Total Capacity:	6,400 lbs.
	Overall Dimensions:	179 11/16” x 102” x 85 1/4” (L x W x H)
	Deck Dimensions:	103 3/4" x 76 5/8” x 23 3/16" (L x W x H)
	Hitch:	3” towing eye, 4 bolt, adjustable, 60,000 lbs. gross trailer weight
	Safety Chains:	3/8” grade 70 chain with 3/8" clevis hooks and safety latches
Running Gear:	Tires:	Size: ST225/75R x 15
	Wheels:	15” x 6” with 6 bolts on a 5.5” bolt circle
	Brakes:	Electric (all wheels)
	Axles:	(2) 5,000 lbs. underslung type
Frame:	Frame Rails:	6” x 4” x ¼” wall tube ASTM A500B
	Cross Members:	6” x 4” x ¼” wall structural steel tube ASTM A500 4” x 2” x 3/16” wall structural tube ASTM A500
Finish:	Hot Dipped Galvanizing	
Reel Carrier:	Turret:	36” diameter, greasable turntable bearings, lockable every 22.5 degrees
	Maximum Reel Width:	54”
	Maximum Reel Diameter:	96”
	Reel Shaft:	2 1/2” diameter with integral power arm, tapered collar, lift point
	Locking Collar:	Galvanized with integral tapered collar and lift point
	Tensioning Brake:	16” ventilated silicon-bronze manual disc brake
Electrical:	Wire Harness:	No internal splices, enclosed in protective loom
	Breakaway System:	To Federal D.O.T. standards with solar maintainer
	Electrical Connection:	7 pin plug
	Lighting/Conspicuity:	LED lighting to Federal D.O.T. standards. Conspicuity tape where practicable
Other:	Tongue jack:	7,000 lb. capacity, drop foot, top wind
	Stabilizer jacks:	(2) adjustable, drop leg, rear mounted
	Registration holder:	Water resistant

Special Features: (2) wheel chocks and holders, aluminum tread plate tool box (24” x 24” x 18”) with lockable paddle latch

MGS Incorporated
178 Muddy Creek Church Rd. Denver, PA 17517 Phone: 800-952-4228 Fax: 717-336-0514 Email:cmcquate@mgsmail.com