UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

CL696T

5.2K Capacity 6" Coil Cager

GENERAL

- GVWR: 11,000 Lbs.
- GAWR: 10,000 Lbs. (*5,000 per axle*)
- Estimated Empty Weight: 5,780 Lbs. (*includes cage & tamer*)
- Total Capacity: 2,600 Lbs.
- Safety Chains: 3/8" Grade 70, with Clevis Hook & Safety Latch
- Hitch: 3" Pintle Eye, Adjustable

DIMENSIONS

- Overall: 308" L x 96" W x 140" H



Trailer shown with optional items

RUNNING GEAR

- Tires: 225/75R15 Ply: Load Range D
- Wheels: Rim: Steel, Bolt Circle: 6 on 5.5"
- Brakes: Electric
- Axles: (2) 5,000 Lbs.

FRAME

- Frame Rails: 8" Steel Channel

ELECTRICAL

- Matched to customer request. (*6-pin min. required*)
- Lighting / Reflectors: To DOT Specifications (*all sealed with rubber isolation mount*)
- Wire Harness: Continuous Protective Loom

FINISH

- Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Polyurethane Two Component High-Solids Enamel

OTHER

- Coil Dimensions: Max with – 60°, Max OD – 132° Min. ID – 68°, Max Weight – 2,600 Lbs.
- Re-rounder: McElroy Line Tamer Capable of Re-rounding 3"-6" IPS, 4-6" Rollers are Standard, 3" Available
- Tongue Jack: 10K Lbs. Top Wind

SPECIAL FEATURES:

- Hydraulic Actuated Cage & Threader Bar for Front
- McElroy 3"-6" LINETAMER® ALT0048 On Sliding Mount
- Rear or Top Loading
- 6 ½" Top Support roller
- Multiple Roller Guides
- Honda 5HP Hydraulic Power Source