UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

ECF20175

19K Fixed Multi-Position Cable Reel Trailer

GENERAL

- GVWR: 25,000 Lbs.
- GAWR: 24,000 Lbs.
- Estimated Empty Weight: 6,500 Lbs.
- Total Capacity: 19,000 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, 60K, 18" – 26" Adjustable
- Safety Chains: 3/8" Grade 70 Chain with Clevis Mount Slip Hook



OVERALL DIMENSIONS

- 31" L x 101" W x 80" H (*62" between uprights*)
- Useable Distance w/ Power Arm & Collar is 57"

RUNNING GEAR

- Tires: ST235/85R x 16 LRE Dual
- Wheels: 16" x 675" 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: (2)12,000 Lbs. Underslung Type

FRAME

- Frame Rails: 10" x 26" Beam ASTM A36
- Cross Members: 7 Gauge HR Sheet ASTM A569

REEL

- Cable Reel Area Approx. 25' L
- Total of 5 Reel Positions w/ Tension Brake Mounting Plates
- (3) 96" Ø or (4) 48" Ø Cable Reels

BRAKES

- Positions for 96" Reels Equipped w/ CCRX Tensioning Brakes
- Tension Brake Capable of 5.5K Ft. torque w/ Guards

ELECTRICAL

- MGS Solar Maintained Breakaway Battery w/ Status Light
- Electrical Connection: 7 Pin Plug Coiled Cord
- Receptacle: J560 w/ Housing
- Lighting / Conspicuity: To D.O.T.: LED, Shock Mounted in Rubber Grommets, Conspicuity Tape
- (2) Taillight System – STT Combined
- Junction Box: MGS #77237

FINISH

- Trailer Finish: Hot Dipped Galvanizing
- All Non-Galvanized Parts – Spectrum Gray

OTHER

- Manual Holder
- Registration Holder: Waterproof