UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

ECF20443

8.8K CAPACITY, 4-REEL CABLE TRAILER

GENERAL

- GVWR: 17,600 Lbs.
- GAWR: 8,000 lbs.
- Estimated Empty Weight 5,500 Lbs.
- Total Capacity: 8,800 Lbs.

DIMENSIONS

- 13'L X 102"W X 22"H (TOP OF FRAME)RUNNING GEAR
- Two Dexter 8,000 Sprung Axles
- Electric Brakes with Full Breakaway System & Solar Maintained Battery
- Tires & Wheels: (4) 215/75R17.5 LRH with steel disc wheels

REEL STANDS

- Four (4) Reels. Two (2) Reels Mounted Side By Side With Two (2) Rows Of Reels.
- The Side-By-Side Reels Are Offset To Allow For Clearance Between Reel Bars And Supports.
- The Center Of The Spindle For The Front Two (2) Reels Is Elevated Above The Rear Two Reels To Allow For Clearance Of The Wire. The Center Of The Spindle Will Be Approx. 30" Above The Trailer Frame.
- The Center Of The Spindle For The Front Two (2) Reels Will Be Approx. 25" Above The Trailer Frame.
- Max. Reel Dim 40" Ø X 30"Wide With A Weight Of 2,000 Lbs.
- The Trailer Supports A Minimum Of Three (3) Rolls Of 750kcm Wire With One Roll Of 350kcm Wire.

REEL SHAFT

- 2.5" Od X .375" Wall Dom Tubing

REEL BRAKE:

- 16" Non-Vented Overspin Brake With Hand Adjustable Caliper

SPECIAL FEATURES

- 3" adjustable towing eye
- Two 3/8" G70 safety chains with 3/8" slip hooks
- 7K Tongue Jack, Two 7K Rear Stabilizer Jacks
- Side Running boards
- Polyurea Deck Coating
- Two ATP 36"L x 24"H x 12"W Side Mount Tool Boxes
- Rear Mounted, Angled Fairlead



ELECTRICAL

- Solar maintained breakaway system to D.O.T
- Peterson LED Lighting to DOT

TRAILER FINISH

- Hot Dipped Galvanized Bed & Chassis
  Non-Galvanized Parts Painted Spectrum Gray