UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EEE20073

11.7K GALVANIZED BATTERY TRAILER



GENERAL

- GVWR: 15,850 Lbs.
- GAWR: 14,400 Lbs.
- Empty Weight: 4,040 Lbs.
- Total Capacity: 11,790 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Lbs. Gross Trailer Weight
- Safety Chains: 3/8" Grade 70 Chain with Clevis Hooks

OVERALL DIMENSIONS

- 219 15/16" L x 96" W x 70 1/2" H
- Deck Dimensions: 108" L x 71" W x 23 ¾" H
- Battery Storage Area: 115" L x 69" W x 38" H

RUNNING GEAR

- Tires: LT235/50R x 16 LRG
- Wheels: 16" x 6" 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: 7,200 Lbs. Underslung Type

FRAME

- Frame Rails: 6 x 4 x ¼" Wall Rectangular Tube ASTM A500B
- Cross Members: 6 x 3 x ¼" Wall Structural Steel Tube ASTM A500

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting and conspicuity to Federal DOT Standards

FINISH

- Body: Hot Dipped Galvanizing
- Battery Storage Area: Spray on Bedliner
- Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment

OTHER

- Tongue Jack: 7K Capacity, Drop Foot, Top Wind
- Registration: Water Resistance

SPECIAL FEATURES

- Enclosed Battery Storage Area w/ Removable Roof Assembly
- Gas Shocks for Door Lift Assist
- Lockable Aluminum Diamond Plate Doors
- 48" x 18" x 24" Aluminum Diamond Plate Toolbox
- Aluminum Control Cabinet w/ Forced Air Circulation
- Wheel Chocks w/ Holders