UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EEE20074

11.9K ENCLOSED BATTERY TRAILER



GENERAL

- GVWR: 5,500 Lbs.
- GAWR: 5,000 Lbs. (*per axle*)
- Empty Weight: 1,950 Lbs.
- Total Capacity: 11,980 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Lbs. Gross Trailer Weight
- Safety Chains: 5/16" Grade 70 Chain with 3/8" Clevis Hooks with Safety Latch

OVERALL DIMENSIONS

- 155" L x 93 W x 58" H
- Deck Dimensions: 94" L x 71" W x 37 1/2" H

RUNNING GEAR

- Tires: ST225/75R x 15 LRD
- Wheels: 15" x 6 Bolts on a 5.5" Bolt Circle
- Brakes: Electric 12" x 12
- Axles: 5,000 Dexter Type

FRAME

- Frame Rails: C6 x 8.2 Structural Channel ASTM A36
- Cross Members: 11 Gauge HR Sheet A569

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting and conspicuity to Federal DOT Standards

FINISH

- Body: Hot Dipped Galvanizing
- Battery Storage Area: Spray on Bedliner
- Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment

OTHER

- Tongue Jack: 7K Capacity, Drop Foot, Top Wind
- Registration: Watertight

SPECIAL FEATURES

- (2) Wheel Chocks and Holders
- Rhino lined Battery Storage Compartment w/ Drain Plugs, Screened Louvers
- Polypropylene storage container for Battery Storage
- Battery Charger rack w/ Polypropylene top
- Aluminum Tread plate Lockable Lid w/ Screened Vents and Gas Springs
- 12V DC (+ and –) Female Panel Mount Receptacles for 300 Amp Plugs
- 120V Shore Connection
- Sealed hinged tailgate w/ rubber lining to accommodate loading of Batteries
- E-track on both sides of Interior
- Interior LED Light
- Tongue mounted Storage Basket
- (4) DOT Flip Placards