UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EMU20006

6.8K Capacity Two Reel / Cargo

GENERAL

- GVWR: 10,000 Lbs.
- GAWR: 5,000 Lbs. (*per axle*)
- Estimated Empty Weight: 3,180 Lbs.
- Total Capacity: 6,820 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Lbs. Gross Trailer Weight
- Safety Chains: 3/8" Chain with Clevis Hooks & Safety Latches

OVERALL DIMENSIONS

- 228 1/2" L x 85" W x 65 11/16" H



RUNNING GEAR

- Tires: ST225/75R x 15 LRD
- Wheels: 15" x 6" Bolts on a 5.5" Bolt Circle
- Brakes: Electric (*all wheels*)
- Axles: (2) 5,000 Lbs. Underslung Type

FRAME

- Frame Rails: 6" x 4"x 3/16" Wall Rectangular Tube ASTM A500B
- Cross Members: 7 Gauge HR Sheet ASTM A569

REEL CARRIER

- Reel Size: (2) 72" Maximum Diameter x 48" Maximum Width
- Reel Shaft: (2) 2 ½" Diameter with Integral Power Arm, Tapered Collar, Lift Point, Removable Sealed Stainless-Steel Bearings & Locking Collar

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway system: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting & Conspicuity to Federal DOT Standards

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: 7000 Lb. Drop Foot, Top Wind
- Registration Holder: Water Resistant

Special Features:

- (2) Reel Bar Storage on Front Outside of Bulkhead
- E-Track Centered Along Both Interior Sides of Bed
- Rear Tailgate
- (3) D-Rings on Each Side
- (2) D-Rings on Front of Trailer