UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EMU20135

6.5K Capacity Pole/Reel/Cargo

GENERAL

- GVWR: 11,500 Lbs.
- GAWR: 10,000 Lbs. (*per axle*)
- Estimated Empty Weight: 3,500 Lbs.
- Estimated Total Capacity: 6,500 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chain: 3/8" Grade 70 Chain with Clevis Hooks & Safety Latches

OVERALL DIMENSIONS

- 175 5/8" L x 102" W x 83.5" H



RUNNING GEAR

- Tires: 245/70R x 17.5 LRH
- Wheels: 17.5" x 6.5", 8 Bolts on 6.5" Bolt Circle, Steel
- Brakes: Electric
- Axles: 10,000 Lbs.

FRAME

- Frame Rails: 6" x 4" x 1/4" Wall Rectangular ASTM A500B
- Cross Members: 6" x 4" x 1/4" Wall Rectangular Tube ASTM A500B

REEL CARRIER

- Estimated Reel Size: 72" Maximum Diameter x 60" Maximum Width
- Reel Shaft: 2 ½" Diameter with Integral Power Arm, Tapered Collar, Lift Point & 16" Ventilated Bronze Manual Disc Tensioning Brake

DECK

- Material: 3/16" Steel Deck Plate ASTM A786, 12ga Side Walls with Horizontal & Vertical Tube Reinforcements. 11" Tailgate Opens to 90° or 180°

ELECTRICAL

- Wire Harness: No Internal Slices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting & Conspicuity to Federal DOT Standards

FINISH

- Prep: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Polyurethane Tow Component High-solids Enamel

OTHER

- Tongue Jack: 7000 Lb. Capacity, Drop Foot, Top Wind
- Stabilizer Jacks: (2) Adjustable Drop Leg, Rear Mounted
- Registration Holder: Water Resistant
- Aluminum Ramps (*fender store*) Ramp Weight is Approx. 17 Lbs. each