UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EMU20246
Telescopic Pole/Cargo

GENERAL



- GVWR: 17,600 Lbs.
- GAWR: 8,000 Lbs. (*per axle*)
- Estimated Empty Weight: 5,480 Lbs.
- Total Capacity: 12,120 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: 3/8" Grade 70 Chain with Clevis Hooks & Safety Latches DIMENSIONS

- Overall - 21.5' L (Extended) – 31' x 96" W x 79 13/16" H

BED

- 129"L x 65.25" x 15" H sides
- 3/16" Floor plate
- Front pole cradle w/two (2) adjustable, self-storing Galvanized pole chocks.
- Two (2) full width bolsters front and rear of axle constructed of Twin C channels

STANCHIONS

- Two (2) sets galvanized, adjustable w/ over-center variable tension cam lock lever. Removable with safety stops at each bolster end.
- Front pole cradle w/two (2) adjustable, self-storing Galvanized pole chocks.

CARGO TIE DOWNS

- One row of E-track installed on each side and front interior sides of the cargo area and front wall as high as possible.

CARGO RESTRAINTS

- Four (4) D-rings per side located on top of the side rail (evenly spaced) w/ capacity rating stamped on each ring.

TAILGATE

- Heavy duty folding tailgate, with chain limiter to allow 90° and 180° open positions.

BINDERS

- Three (3) heavy duty, ratchet type binder w/ 4 in. W x 20 ft. (min) L nylon strap with flat hook end installed at each bolster. Binder release extension to keep operator's fingers away from ratchet teeth. PVC lined pole hubs on bolsters allow pole wrap

TELESCOPIC TONGUE

- 8" x 8" extendible tongue w/ heavy duty reinforcement. Sintered bronze bushings. Five (5) adjustment extendable tongue positions. Tongue lock – 1-1/4in. yellow MGS zinc chromate plated pin. Safety retainer latch and retainer chain. "Cat-Track" system that extends and retracts the electrical wiring inside of the tongue.

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting & Conspicuity to Federal DOT Standards

FINISH

- Hot Dipped Galvanizing
-

LANDING GEAR

- (2) 10,000# trunnion mount, side wind jacks. 6" x 8" Sand shoe – 21" travel, Left side of telescoping tongue; (1) right side pull frame.
- Stabilizer Jacks: (2) Adjustable Drop Leg, Rear Mounted
- Registration: Water Resistant