UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EMU20254-GR

10K Capacity Twin Reel/Cargo Retriever with Gas Powered HPU

GENERAL

- GVWR: 15,400 Lbs.
- GAWR: 7,000 Lbs. (*per axle*)
- Estimated Empty Weight: 5,100 Lbs.
- Total Capacity: 10,300 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: 3/8" Grade 70 Chain with Clevis Hooks & Safety Latches

OVERALL DIMENSIONS

- 19.25' L x 96" W x 79 13/16" H

RUNNING GEAR

- Tires: LT235/85R16 LRG
- Wheels: 16" x 6", 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: 7,000 Lbs. Underslung Type

FRAME

- Frame Rails: 6" x 4" x 1/4" Wall Rectangular Tube ASTM A500B
- Cross Members: 6" x 4" x ¼" Wall Rectangular Tube ASTM A500B

REEL CARRIERS

- Reel Size: 72" Maximum Diameter x 66" Maximum Width
- Spindle Shaft: 2 ½" Diameter with Integral Power Arm, Tapered Collar, Lift Point & 16" Ventilated Bronze Manual Disc Brake
- Cable retriever with directional control powered by 5.6 HP Gas Engine
- Drive and freewheel clutch

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting & Conspicuity to Federal DOT Standards

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: 7,000 Lbs. Capacity, Drop Foot, Top Wind
- Stabilizer Jacks: (2) Adjustable Drop Leg, Rear Mounted
- Registration: Water Resistant



OPTIONS

- (2) Wheel Chocks & Holders
- Reel Bar Storage on Both Sides
- Reel Coupling Brackets / Storage Brackets
- Toolbox
- (4) D-rings on each Side