UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

# EPT20141

## 14K Capacity Telescopic Pole Trailer

GENERAL

- GVWR: 18,000 Lbs.
- GAWR: 15,000 Lbs.
- Estimated Empty Weight: 3,850 Lbs.
- Total Capacity: 14,000 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Lbs. Gross Trailer Weight with 18" Hitch Extension
- Safety Chains: ½" Grade 70 Chain with Clevis Hooks & Safety Latch



OVERALL DIMENSIONS

- 247" L x 90" W

RUNNING GEAR

- Tires: ST215/75R x 17.5 LRH, Good Year Brand
- Wheels: 17.5" x 6.75" Dual with 8 Bolts on a 275mm Bolt Circle
- Brakes: Electric
- Axles: 15,000 Lbs. Underslung Type

FRAME

- Frame Rails: 10" x 4"x 1/4" Wall Structural Tube ASTM A500B
- Cross Members: ¼" HR Plate ASTM A36, 2" x 3/16" Wall Structural Tube ASTM A500B

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway system: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: Coiled Cord Wired to J560 Spec
- Lighting / Conspicuity: LED to DOT

FINISH

- Hot Dipped Galvanizing
- Non-Galvanized Parts – Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Polyurethane Tow Component High-Solids Enamel

OTHER

- Tongue Jack: 7000 Lb. One on "A" Frame & One on Telescopic Tongue
- Registration Holder: Truck Lite
- Hitch Extension: 12" – 24" Available

Special Features:

- Tongue extends 10', Bronze Bushings on Tongue Receiver
- Integral Light Bar with Ratchet Strap & 25' Cord
- Flexible Cable Carrier to Protect Tongue Wiring
- Winch Handle, (3) 4" Pole Binders with Ratch Type Heavy Duty 6,000 lb. Winch
- (4) Adjustable Pole Stanchions
- Pole Chocks on Front Bolster
- Wheel Chock Holder
- Manual Holder