UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

EPT20260

28K CAPACITY TELESCOPIC POLE TRAILER

GENERAL

- GVWR: 34,000 Lbs.
- GAWR: 4 5 ,000 Lbs.
- Estimated Empty Weight: 6,000 Lbs.
- Total Capacity: 28,000 Lbs.
- Hitch: 3” Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: 3/8” Grade 70 Chain with Clevis Hooks & Safety Latches

OVERALL DIMENSIONS

- Collapsed = 37'3" L x 6'9"W x 38"H(deck)
- Extended = 62'8"

RUNNING GEAR

Tires: 255/70R22.5 Goodyear

- Wheels: 22.5X8.25Dual 10 on 285.75mm 6.6
- Brakes: Air /ABS/ both axles 4S,2M crosslinked
- Lines run through tongue in "Cat Track"
- spring brakes and auto slack adjusters
- Spring brake release Included
- Axles: Dexter 22.5 K sprung with Hutcheson suspension (H-9700) FRAME
- Frame Rails: 6” x 4” x 1/4” Wall Rectangular Tube ASTM A500B
- Cross Members: 6” x 4” x ¼” Wall Rectangular Tube ASTM A500B

REAR TELESCOPIC

- 4" x 6 x .188" structural tube (2) Internal and external Rollers
- Deck: Front recessed storage area A-frame to suspension w/expanded metal floor
- Tread plate over fender area 3/16"

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED Lighting & Conspicuity to Federal DOT Standards

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: Two 10,7,000 Lbs. Capacity, Drop Foot,
- Registration: Water Resistant