



UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228

Web: MGSUtilityFleet.com



# ESR20059

## 8.6K Capacity Substation Recovery Trailer

### GENERAL

- GVWR: 15,400 Lbs.
- GAWR: 7,000 Lbs. (*per. axle*)
- Empty Weight: 6,760 Lbs.
- Total Capacity: 8,640 Lbs.
- Unladen Hitch Weight: 600 Lbs.
- Hitch: 2 5/16" Ball Coupler, 4 Bolt Adjustable, 25K Gross Trailer Weight
- Safety Chains: 3/8" G7 with 3/8" Clevis Hooks & Safety Latch

### OVERALL DIMENSIONS

- 270 3/8" L x 96" W x 83 5/8" H

### RUNNING GEAR

- Tires: 235/85R16 LRG
- Wheels: 16 X 6" with 8 bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: 7,000 Lbs. Underslung Type

### FRAME

- Frame Rails: 6" x 4" x 1/4" Wall Rectangular tube ASTM A500B
- Cross Members: 6" x 3" x 3/16" Structural Steel Channel ASTM A1011

### ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway system: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Way Plug
- Lighting / Conspicuity: LED to DOT Standards. Conspicuity Tape where Practicable

### FINISH

- Hot Dipped Galvanizing

### OTHER

- Tongue Jack: 7000 Lb. Capacity, Drop Foot, Side Wind
- Registration Holder: Water Resistant

### Special Features:

- Rear Stabilizer
- (3) Poly coated Steel Rollers with Bronze Bearings
- Reel Tarp & HPU Tarp
- Manual Retrieve Capability
- 48" x 24" x 36" Aluminum Diamond Plate Toolbox

