UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

GCT10048

1.9K Capacity Tilting Coiled Pipe

GENERAL

- GVWR: 3,500 Lbs.
- GAWR: 3,500 Lbs.
- Estimated Empty Weight: 1,550 Lbs.
- Total Capacity: 1,950 Lbs.
- Safety Chains: 3/8" Grade 43 with 3/8" Clevis Hooks
- Hitch: 3" Eye, Adjustable Channel



DIMENSIONS

- Overall: 150" L x 102" W x 82" H

RUNNING GEAR

- Tires: 205/75R 15LRC
- Wheels: 15" X 5 JJ with 5 Bolts on 4.5" Bolt Circle
- Brakes: Electric
- Axles: Torflex 22 ½ Down. Galvanized Finish

FRAME

- Formed: 7GA HR ASTM A1011
- Tongue Formed: 7GA HR ASTM A1011
- Cross Members: Rear – ¼" HR Steel ASTM A36
- Cross Members: Center – 4" x 4" x 1/8" Tube

CAROUSEL

- 102" OD
- (3) Removable 2" x 2" Vertical ID Posts Located with Spring Pins
- ID Posts Adjust to Accommodate 36" – 58 ½" Coil ID's
- 6K Stub Axle with Adjustable Payout Brake

TILT/HYDRAULICS

- 90° Tilt via Electric/Hydraulic Pump
- Umbilical Remote with Up/Down Controls
- Black, Powder Coated, Steel, Lockable Enclosure

ELECTRICAL

- Connection: SAE J560
- Lighting/Conspicuity: LED – To Federal DOT 4 Taillight System
- Breakaway System: Lead/Acid Sealed Battery
- Wire Harness: No Internal Splices, Enclosed in Protective Loom

FINISH

- Hot Dipped Galvanized

OTHER

- Tongue Jack: 7K Capacity Drop Foot, Top Crank
- Registration Holder: Water Resistant
- Rear Stabilizers: (2) Drop Down Located at Rear Corner



SPECIAL FEATURES:

- Two Rear Mount Tracer Wire Holder Locations
- Capable of Carrying 3" Pipe
- Optional McElroy 2" LINETAMER® LTO122