UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

# GSP10061

## 18K Capacity Stick Pipe

GENERAL

- GVWR: 24,000 Lbs.
- GAWR: 12,000 Lbs.
- Estimated Empty Weight: 5,951 Lbs.
- Total Capacity: 18,059 Lbs.
- Hitch: 3" Lunette Eye, 3 Position Adjustable, 18.5 – 27.5"
- Safety Chains:



OVERALL DIMENSIONS

- 48'-6" L x 102" W x 62" H
- Deck Dimension: 41' L x 102" W x 38" Bunk Height

RUNNING GEAR

- Tires: LT235/75R 17.5 LRH
- Wheels: 17.5 x 6.75 – 8 on 6.5
- Brakes: Electric
- Axles: 12,000 Lbs. HD Dexter Sprung Axles with Rubber Bushed Suspension & Slipper Springs

FRAME

- Frame Rails: W12 x 19 Wide Flange Beam ASTM A992
- Cross Members: Formed ¼" x 34-1/4" x 37.75"

ELECTRICAL

- Wire Harness: Automotive Grade Modular Harness with Front & Rear Mounted Junction Box
- Breakaway System: SLA Battery & Switch to DOT
- Electrical Connection: J560
- Lighting / Conspicuity: LED in Rubber Shock Mount (4 Taillight System)

TONGUE BASKET

- Material: ¾" - #9 Flattened Expanded Metal
- Dimensions: 60-3/4" x 34-1/4" x 37.75"

POLEBOLSTERS

- Material: Center 5 – Bolsters, Constructed from C6 x 8.2 Structural Channel ASTM A36
- Front & Rear Bolsters 6" x 3" x 3/16" Structural Steel Tube ASTM A500 GRB
- Stanchions: 10-MGS 134154 Galvanized Adjustable 24" H – Two per Bolster with Stop Bolts

BINDERS

- 5- 4" W x 27' L 5K Nylon Straps on Ratchet Binders with Safety Release (1) Winch Bar Included

FINISH

- Preparation: Iron Phosphate Conversion Treatment, Chromium Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Single Stage PPG Polyurethane (*yellow*)

OTHER

- Tongue jack: 10K Lift, 12K Static
- Registration Holder: Truck Lite Waterproof