UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

ECT20000

3.6K Capacity Twin Reel Single

GENERAL

- GVWR: 6,600 Lbs.
- GAWR: 6,000 Lbs.
- Estimated Empty Weight: 2,840 Lbs.
- Total Capacity: 3,600 Lbs.
- Hitch: 3" Towing Eye, Adjustable, 12K Lbs. Gross Trailer Weight
- Safety Chains: 3/8" Grade 43 Chain with Clevis Hooks & Safety Latches



OVERALL DIMENSIONS

- 180 11/16" L x 96 ¾" W x 77 ¾" H

RUNNING GEAR

- Tires: ST235/80R x 16 LRE
- Wheels: 16" x 6" 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: 6,000 Lbs. Overslung type

FRAME

- Frame Rails: C8 X 11.5 Structural Channel ASTM A36
- Cross Members: 7 Gauge HR Sheet ASTM A569, 4" x 2" x 3/16" Wall Structural Steel Tube

REEL CARRIER

- Dimensions: 2 ½" Diameter Hot Dipped Galvanized Steel Tube Standard, Reel Lock with Integral Tapered Bushing

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway system: To Federal DOT Standards
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED to Federal DOT Standards. Conspicuity Tape Where Practicable

FINISH

- Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
- Primer: Epoxy Ester High Solids Primer
- Topcoat: Polyurethane Two Component High-Solids Enamel

OTHER

- Tongue Jack: 10,000 Lb. Capacity, Drop Foot, Top Wind
- Stabilizer Jacks: (2) Adjustable Drop Leg, Rear Mounted
- Registration Holder: Water Resistant