UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

ECT20152

19K Capacity Triple Turret

GENERAL

- GVWR: 30,000 Lbs.
- GAWR: 15,000 Lbs. (*per axle*)
- Estimated Empty Weight: 11,000 Lbs.
- Turret Capacity: 8,000 Lbs. (*per turret*)
- Total Capacity: 19,000 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Lbs. Gross Trailer Weight, 12" Hitch Extension 60K
- Safety Chains: 3/8" Grade 70 Chain with ½" Clevis Hooks & Safety Latches



DIMENSIONS

- Overall: 370" L x 96" W
- Deck Dimensions: 281" L x 68 1/8" W x 33 ¾" H

RUNNING GEAR

- Tires: ST215/75R 17.5 Dual
- Wheels: 17.5" x 6.75" 8 Bolts on a 275mm Bolt Circle
- Brakes: Electric (*all wheel*)
- Axles (2) 15K Lbs. Underslung Type

FRAME

- Frame Rails: 10" x 4" x ¼" Tube ASTM A500B
- Cross Members: 10" x 4" x ¼" Tube ASTM A500

REEL CARRIER

- Turret: (3) Turrets on 36" Greaseable Turntable Bearings Lockable on 22.5° (*RS controls*)
- Useable Spindle Width: 56"
- Maximum Reel Diameter: 96"
- Reel Shaft: (3) 2 ½" Diameter with Integral Power Arm, Tapered Collar, Lift Point, Clam Shell Roller Bearing Reel Bar Mounts
- Locking Collar: (3) Galvanized with Integral Tapered Collar & Lift Point
- 16" Ventilated Silicon-Bronze Manual Disc Brake

DECK

- NON-Skid: Deck Plates Coated with Truck Bed Liner with Aggregate Added
- D-Rings: (4) Per Side Located on Side of Deck
- Storage Basket: Curb Side Expanded Metal for Gathering Sock & Misc. Storage
  "A" Frame Mounted Expanded Metal Open Top
- Access: Roadside Fold Out Steps & Folding Handrails Provide Three Points of Contact

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway system: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Pin Plug
- Lighting / Conspicuity: LED to Federal DOT Standards. Conspicuity Tape Where Practicable

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: Dual 10K Lbs. Capacity, Drop Foot, Side Wind, Cross Linked Crank
- Stabilizer Jacks: (2) Adjustable Drop Leg, Rear Mounted
- Registration Holder: Water Resistant