UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

UOP30029

17.3K Capacity Equipment Trailer

GENERAL

- GVWR: 24,446 Lbs.
- GAWR: 11,112 Lbs. (*per axle*)
- Estimated Empty Weight: 7,146 Lbs.
- Total Capacity: 17,300 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: 3/8" Grade 70 Chain with 3/8" Clevis Hooks & Safety Latches

OVERALL DIMENSIONS

- 386 13/16" L x 96" W x 86" H
- Deck Dimension: 228 ¼" with 60" Beaver Tail L x 96" W x 33 ¼" H

RUNNING GEAR



- Tires: LT235/85R16 LRE Dual
- Wheels: 16" x 6" Dual with 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: (2) 12,000 Lbs. Underslung Type

FRAME

- Frame Rails: W12 x 16 I-Beam ASTM A572 Grade 50
- Cross Members: M6 x 4.4 Junior I-Beam

DECK

- Material: Rough Cut Oak, 2" Normal Thickness
- Beaver Tail: 10° Angle

RAMPS

- Dimensions: 60" L x 19" W,
- Steel Construction, Vertical Store, Spring Assist
- Loading Angle 15°

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Way Plug
- Lighting / Conspicuity: LED Lighting to Federal DOT Standards, Conspicuity Tape Where Practicable

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: 20K Lbs. Capacity, Drop Leg, Dual Pin
- Registration Holder: Truck Lite Water Resistant

SPECIAL FEATURES

- Toolbox Mounted in Tongue with Expanded Metal Floor & Lockable Lid