UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

UOP30030

30K Capacity Utility Full-Tilt



GENERAL

- GVWR: 39,952 Lbs.
- GAWR: 18,160 Lbs. (*per axle*)
- Estimated Empty Weight: 9,230 Lbs.
- Total Capacity: 30,452 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: 1/2" Grade 70 Chain with Clevis Hooks & Safety Latches

OVERALL DIMENSIONS

- 397" L x 96" W x 86" H
- Deck Dimension: 20' + 6' Beaver Tail L x 8' W x 35 ¼" H

RUNNING GEAR

- Tires: 215/75R17.5 LRE Dual
- Wheels: 17.5" x 6.75" Dual with 10 Bolts on a 8.75" Bolt Circle
- Brakes: Air with ABS (2 Sensors, 1 Modulator) & Auto Slack Adjusters
- Axles: (2) 20,000 Lbs. Underslung Type

FRAME

- Frame Rails: W14 x 26 Wide Flange Beam ASTM A572 Grade 50
- Cross Members: M6 x 4.4 Junior I-Beam

DECK

- Rough Cut Oak, 2" Normal Thickness
- Beaver Tail, Self-Cleaning, 8° Angle

RAMPS

- Dimensions: 60" L x 19" W
- Aluminum Construction, Vertical Store with Chain Traps & Chain
- Loading Angle 15°

LOADING ANGLE

- Tilted: 4° Via Dual Fulcrum (*tongue / suspension*)

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Electrical Connection: 7 Way Plug
- Lighting / Conspicuity: LED Lighting to Federal DOT Standards, Conspicuity Tape Where Practicable

FINISH

- Hot Dipped Galvanizing
- Non-Galvanized Parts:
  - Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
  - Primer: Epoxy Ester High Solids Primer
  - Topcoat: Polyurethane Two Component High-Solids Enamel

OTHER

- Tongue Jack: 25K Lbs. Capacity, 2 Speed Drop Foot, Side Crank
- Registration Holder: Water Resistant

SPECIAL FEATURES

- Aluminum Toolbox Mounted to Headboard
- Monorail Tongue