UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

U0P30031

33K Capacity Utility Tilt-Bed

GENERAL

- GVWR: 44,000 Lbs.
- GAWR: 15,000 Lbs. (*per axle*)
- Estimated Empty Weight: 10,710 Lbs.
- Total Capacity: 33,290 Lbs.
- Unladen Hitch Weight: 950 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: ½" G70 with Clevis Hooks & Safety Latches



OVERALL DIMENSIONS

- 424 1/2" L x 96" W x 37 1/2" H
- Deck Dimension: 264" + 72" Beaver Tail L x 96" W x 33 3/8" H

RUNNING GEAR

- Tires: 215/75R 17.5 LRH Dual
- Wheels: 17.5" x 6.75" with 8 Bolts on a 275mm Bolt Circle
- Brakes: Air with Auto Slack Adjusters & Spring Breaks
- Axles: 15,000 Lbs. Underslung Type

FRAME

- Frame Rails: W14 x 26 Wide Flange Beam ASTM A572 Grade 50
- Cross Members: M6 x 4.4 Junior I-Beam

DECK

- Material: Rough Cut Oak, 2" Normal Thickness
- Beaver Tail: 8° Angle

RAMPS

- Dimensions: 60" L x 19" W
- Aluminum Construction, Vertically Stored with Chain Traps & Chain
- Loading Angle 15°

LOADING ANGLE

- Tilted: 4° Via Dual Fulcrum (*tongue / suspension*)

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards with Solar Maintainer
- Electrical Connection: 7 Way Plug
- Lighting / Conspicuity: LED Lighting to Federal DOT Standards, Conspicuity Tape Where Practicable

FINISH

- Hot Dipped Galvanizing
- Non-Galvanized Parts:
  - Preparation: Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
  - Primer: Epoxy Ester High Solids Primer
  - Topcoat: Polyurethane Two Component High-Solids Enamel

OTHER

- Tongue Jack: 25K Lbs. Capacity, 2 Speed Drop Foot, Side Crank
- Registration Holder: Water Resistant

SPECIAL FEATURES

- Aluminum Toolbox Mounted (*30" L x 18" W x 14" H*) to Headboard
- (1) Fold Out Step
- Monorail Tongue