UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

UOP30038

15.6K Transformer Hauler Trailer

GENERAL

- GVWR: 19,800 Lbs.
- GAWR: 9,000 Lbs. (*per axle*)
- Estimated Empty Weight: 4,200 Lbs.
- Total Capacity: 15,600 Lbs.
- Hitch: 3" Towing Eye, 4 Bolt, Adjustable, 60K Gross Trailer Weight
- Safety Chains: 3/8" Grade 70 Chain with ½" Clevis Hook & Safety Latches

OVERALL DIMENSIONS

- 210 3/16" L x 96" W x 42 1/2" H
- Deck: 148 ½" L x 91 ½" W x 33 ½" H



DECK

- Material: 3/16" Thick Steel Diamond Floor Plate ASTM A786

RUNNING GEAR

- Tires: ST215/75R x 17.5 LRH
- Wheels: 17.5" x 6.75" 8 Bolts on a 6.5" Bolt Circle
- Brakes: Electric
- Axles: (2) 9,000 Lbs. Underslung Type

FRAME

- Frame Rails: C10 x 15.3" Structural Channel ASTM A36
- Cross Members: 7 Gauge HR Sheet ASTM A569

ELECTRICAL

- Wire Harness: No Internal Splices, Enclosed in Protective Loom
- Breakaway System: To Federal DOT Standards w/ Solar Maintainer
- Electrical Connection: 6 Way Plug
- Lighting / Conspicuity: LED Lighting & Conspicuity to Federal DOT Standards

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: 10K Capacity, Drop Foot, Top Wind
- Registration Holder: Waterproof

SPECIAL FEATURES

- (2) Wheel Chocks & Holders
- Expanded Metal Lined Tongue Area
- Rub Rail w/ Tie Down Pockets
- (6) Recessed Swiveling tie Downs w/ 6K Capacity/ each
- 5/4" x 6" Poly Lumber Sides w/ 2" x 4" Anchors (*on all four sides of deck*)
- (4) D-Rings (*2 on each side of trailer*)