UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

UOP30045

53K Telescopic Pole Trailer

GENERAL

- GVWR: 68,000 Lbs.
- GAWR: 23,360 Lbs.
- Estimated Empty Weight: 15,000 Lbs.
- Total Capacity: 53,000 Lbs.
- Hitch: 2" King Pin
- Landing Gear: (2) 50,000 Lbs. 2 Speed Landing Gear w/ Connecting Pipe

OVERALL DIMENSIONS

- 175 5/8" L x 102" W x 79 13/16" H



RUNNING GEAR

- Tires: 11R22.5 LRG
- Wheels: 22.5" x 8.25" Dual with 10 Bolts on a 285.75mm Bolt Circle
- Brakes: Air w/ABS. Spring Brakes and Auto Slack Adjusters
- Axles: (2) 25,000 Lbs., Overslung

FRAME

- Rear Section Frame Rails: W18 x 40 Beam ASTM A992
- Front Section Frame Rails: W16 x 40 Beam ASTM A992
- Cross Members: 7 Gage HR Sheet ASTM A1011 DECK
- Material: 1 5/16" x 7" Apitong Hardwood w/4x4 Oak Pole Rests

ELECTRICAL

- Wire Harness: Telescopic Section Enclosed in "Cat Track"
- No Internal Splices – Enclosed in Protective Loom
- Electrical Connection: 7 Pin Receptacle
- Lighting / Conspicuity: LED and conspicuity to D.O.T. FINISH
- Hot Dipped Galvanizing – Entire Chassis & Body
- Non-Galvanized Parts:
  - o Iron Phosphate Conversion Treatment, Chromium-Free Post Treatment
  - o Primer: Epoxy Ester High Solids Primer
  - o Topcoat: Polyurethane Two Component Hight Solids Enamel

OTHER

- Registration Holder – Water Resistant SPECIAL
- Trailer Extends in 5' Increments from 40' – 55'
- Telescopic Frame Rides on (4) 6" Ø x 2" 1018 Steel, Greaseable, Rollers
- Flexible Carrier (Cat-Track) Protects Wire Harness & Air Lines During Telescopic Movements
- Air Latch & Release Telescope w/ Safety Latches
- (8) Adjustable Stanchions Drop flush to Deck for Side Unloading & Loading
- (4) Tiedown Straps 4" x 27' w/ Chain anchors & Ratchet Binders
- (2) Ingress / Egress Steps (folding) w/ Removable Handrails (one on each side of deck)
- Frame Mounted ATP Toolbox (48" x 18" x 18") side Open w/ Automotive Seals & Loc