UTILITY FLEET SOLUTIONS | 178 Muddy Creek Church Rd. Denver, PA 17517

Phone: 800.952.4228 Web: MGSUtilityFleet.com

U0P30162

14.8K Capacity Tilt, Beaver Tail TVH

GENERAL

- GVWR: 20,000 Lbs.
- GAWR: 9,610 Lbs. (*each axle*)
- Estimated Empty Weight: 5,200 Lbs.
- Total Capacity: 14,800 Lbs.
- Hitch: Adjustable 3" Towing Eye, 4 Bolt 60K Capacity
- Safety Chains: 3/8" G70 with G70 Clevis Mount Slip Hook



DIMENSIONS

- Overall: 288.5" L x 96" W x 36.25" H
- Deck Dimension: 215.5" L x 96" W
- Beavertail: 2' L

DECK

- 32" Wide, #5 Expanded Steel Grating
- Traction Assist: (4) Each bolt on Inverted Channel Traction Cleats Attached to Beavertail
- 28.5" Open Deck center
- 5.75" H Tapered Inner Track Guides Welded to Bed Center
- Bed Tilts Via Hydraulic Cushion Cylinder With Lock
- (3) D-Rings per Side, (2) Rear
- (4) Pivoting Web Winches (2) Front and (2) Rear
- Breaker Bar Included
- (4) Slide out Marker Lights
- (2) Blade Rests Shipped Loose for Precise Positioning

RUNNING GEAR

- Tires: ST215/75R17.5 LRH
- Wheels: 17.5" x 6.75" Steel Wheels, 8 on 6.5" Bolt Pattern
- Brakes: Electric, FSA
- Axles: Dexter D100HD Sprung
- Spare Tire Carrier: Located Under Tongue
- Suspension: Multi-Leaf, Rubber Bushed, Slipper

FRAME

- Frame Rails: C10 x 20 structural channel ASTM A36
- Crossmembers: 6 x 3 x 3/16 Wall Rectangular Steel Tube ASTM A500 B
- A Frame Mounted Tool Box

ELECTRICAL

- Wire Harness: Color Coded Sealed Modular System
- Breakaway System: 12V Sealed Lead Battery in Protective Case, Mounted
- Electrical Connection: 7 Way Receptacle with 12' Coiled Cord J560 Plug Ends
- Lighting / Conspicuity: To DOT requirements. Four Tail Light, Sealed LED Lights, Reflectors, Conspicuity Tape

FINISH

- Hot Dipped Galvanizing

OTHER

- Tongue Jack: 10K Capacity, Side Crank, Drop Leg with Integral Sand Foot
- Registration Holder: Located in Tongue Area

SPECIAL FEATURES

- Tongue Length: 48" (*to hitch plate*)
- Splash Guards: Located Over Tires
- Mud Flaps: (2) 10" x 22" Anti-Sail